

Specifications

Model Number		Eco
Rated Voltage		AC 120V, 60Hz
Rated Power		1140W
Length of Power Cord		36 inches
Circuit Breaker		Within 10mA 0.1 second
Wash	Posterior	0.17 gal/min
	Front	0.17 gal/min
	Heat Capacity	1140W
	Safety Feature	Temperature Switch
Dry	Air Temperature	Room temperature ~ 131°F (approximately)
	Heat Capacity	140W
	Safety Feature	Thermal Fuse, Bimetal
Heated Seat	Seat Temperature	82.4°F ~ 104°F (approximately)
	Heat Capacity	30W
	Safety Feature	Thermal Fuse
Fire Protection	Seat	5VA
	PCB Borad Shell	V-0
Water Supply	Connection	Direct connection to water supply
	Water Pressure (required)	11.6 psi ~ 101.5 psi (incoming)
Dimensions	Elongated Seat	20.43 inches x 17.72 inches x 5.24 inches



IAPMO Uniform Plumbing Code (UPC) Certification Mark: The International Association of Plumbing and Mechanical Officials (IAPMO) Shield is applied to products that are certified by IAPMO as complying with BOTH the product's performance standard AND the Uniform Plumbing Code (UPC). Applies to all plumbing products, appliances, pipe, fixtures, valves and related products.