

Product Specifications

Item		GB-4000-EW • GB-4000-RW	GB-5000-EW • GB-5000-RW
Power Supply		120V~, 60Hz	
Max. Power Consumption		660W	
Length of Power Cord		3.94ft (1.2m)	
Water Supply Connection		Direct connection to the water supply	
Water Supply Pressure		14.223psi~106.675psi (98 - 735kPa)	
Cleansing	Water Flow Rate	Cleansing	Max. 0.251gal/min (0.95 ℓ /min)
		Bidet	Max. 0.251gal/min (0.95 ℓ /min)
	Water Pressure Adjustment	5 Levels	
	Temp. Adjustment	Normal Temp., 93.2°F(34°C), 98.6°F(37°C), 104°F(40°C)	
	Heater Capacity	600W	
	Safety Device	Thermal Fuse, Thermostat, Water Level Sensor	
Warm Seat	Temp. Adjustment	Normal Temp., 95°F(35°C), 100.4°F(38°C), 104°F(40°C)	
	Heater Capacity	55W	
	Safety Device	Thermostat	
Dry	Temp. Adjustment	Normal Temp. ~ 122°F(50°C) (5 Levels)	
	Heater Capacity	195W	
	Safety Device	Thermal Fuse, Bi-metal	
Water Supply Temp.		37.4°F(3°C) ~ 95°F(35°C)	
Temp. of circumstance for use		37.4°F(3°C) ~ 104°F(40°C)	
Product size	Elongated	1.52ft(W) x 1.74ft(L) x 0.51ft(H) (462mm x 530mm x 155mm)	1.26ft(W) x 1.74ft(L) x 0.51ft(H) (385mm x 530mm x 155mm)
	Round Front	1.52ft(W) x 1.62ft(L) x 0.51ft(H) (462mm x 495mm x 155mm)	1.26ft(W) x 1.62ft(L) x 0.51ft(H) (385mm x 495mm x 155mm)
Product weight	Elongated	9.70lbs(4.4kg)	9.04lbs(4.1kg)
	Round Front	9.48lbs(4.3kg)	8.82lbs(4.0kg)