







Giving Shape to Ideas

CUSTOMER BENEFITS



2

Intuitive operability Operate the bizhub like a smartphone or tablet with fully customised user interface

Mobile connectivity Print anytime from anywhere Secure n with Konica Minolta's innovative mobile technologies advanced

4 MEDIA INPUT

Copier desk DK-516

Banner tray BT-C1e

2 x Universal tray

Large capacity tray PC-416

Large Capacity tray LU-302 Security Secure network integration, data encryption and advanced user authentication

Application ecosystem Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio



Productivity Reliability, high-speed scanning and printing, combined with powerful finishing functions cor m

Sustainability Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup

CONNECTIVITY	
Fax board FK-514	2
Wireless LAN UK-221	
USB I/F kit EK-608	DR
USB I/F kit EK-609	K
Fiery controller IC-420	
Interface kit VI-516	
Interface board UK-115	
ID card reader	
Mount kit MK-735	

CONNECTIVITY	
FK-514 Fax board	Super G3 fax, digital fax functionality
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
IC-420 Fiery controller	Professional colour print controller
VI-516 Interface kit for IC-420	Fiery controller interface card
UK-115 Interface board for IC-420	Fiery controller interface board
ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader

TECHNICAL SPECIFICATIONS

bizhub C360i/C300i/C250i Datasheet

SYSTEM SPECIFICATIONS	
Panel size/resolution	10.1" / 1024 x 600
System memory (standard/max)	8 GB
System storage	256 GB Solid State Drive (standard)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n (optional)
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP;
	HTTP(S); AppleTalk; Bonjour
Automatic document feeder	Up to 100 originals; A6–A3; 35–163 g/m ² ;
	RADF or Dualscan ADF available
Paper input capacity (standard/max)	1,150 sheets / 6,650 sheets
Paper tray input (standard)	1x 500 sheets; A6-A3; custom sizes; 52-256 g/m ²
	1x 500 sheets; A5-SRA3; custom sizes; 52-256 g/m ²
Paper tray input (optional)	2x 500 sheets; A5-A3; 52-256 g/m ²
	1x 2,500 sheets; A4; custom sizes; 52-256 g/m ²
Large capacity tray (optional)	1x 3,000 sheets; A4; custom sizes; 52-256 g/m ²
Manual bypass	150 sheets; A6–SRA3; Custom sizes; Banner; 60–300 g/m ²
Automatic duplexing	A5-SRA3; 52-256 g/m ²
Finishing modes (optional)	Offset; Group; Sort; Staple; Punch; Half-fold; Letter-fold; Booklet
Output capacity (standard)	Max. 250 sheets
Output Capacity (optional)	Max. 3,300 sheets
Stapling	Max. 50 sheets or 48 sheets + 2 cover sheets (up to 209 g/m^2)
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 30 sheets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 209 g/m ²)
Booklet output capacity	Max. 100 booklets; unlimited (without tray)
Copy/print volume (monthly)	C360i Rec. 33,000 pages; Max. ¹ 175,000 pages
	C300i Rec. 25,000 pages; Max. ¹ 150,000 pages
	C250i Rec. 16,000 pages; Max. ¹ 130,000 pages
Toner lifetime	Black up to 28,000 pages
	CMY up to 28,000 pages

OPTIONS



3 OTHERS

DF-632 Document feeder DF-714


Working table WT-506

10-Key pad KP-102

Security kit SC-509

Keyboard holde





LEGEND Mandatory option Option This option can only be installed with the respective option above it

FINISHING FUNCTIONALITIES



DESCRIPTIONS

ENHANCED FEATURES

LK-102v3 PDF enhancements LK-105v4 OCR text recognition

3

5	
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX; XLSX and PDF/A
LK-111 ThinPrint [®] Client	Print data compression for reduced network impact
LK-115v2 TPM activation	Trusted Platform Module for protection of data
	encryption and decryption
LK-116 Antivirus	Bitdefender® Antivirus provides real time scanning
	of all in-/outcoming data
CONNECTIVITY	
FK-514 Fax board	Super G3 fax, digital fax functionality
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode

Searchable PDF and PPTX

PDF/A (1b); PDF encryption; digital signature

OTHERS

DF-632 Document feeder	Reversing automatic document feeder, capacity 100 originals
DF-714 Document feeder	Dualscan automatic document feeder, capacity 100 originals
WT-506 Working table	Authentication device placement
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function (2 kits required for Dualscan ADF)
KH-102 Keyboard holder	To place USB keyboard

MEDIA INPUT

PC-216 2x Universal tray	2x 500 sheets, A5-A3, 52-256 g/m ²
PC-416 Large capacity tray	2,500 sheets, A4, 52-256 g/m ²
LC-302 Large capacity tray	3,000 sheets, A4, 52-256 g/m ²
BT-C1e Banner tray	Multipage banner feeding
DK-516 Copier desk	Provides storage space for print media and other materials

MEDIA OUTPUT

50-sheet stapling, 500 sheets max. output
2/4 hole punching, autoswitching
50-sheet stapling, 3,300 sheets max. output
50-sheets staple finisher; 20-sheets booklet finisher;
2,300 sheets max. output
2/4 hole punching; autoswitching
For FS-536(SD)/FS-537(SD) installation,
(Max. 100 sheets output capacity)
Separation of fax output; etc.

Imaging unit lifetime	C360i: Black up to 225,000/1,000,000 pages (drum/developer) CMY up to 105,000/1,000,000 pages (drum/developer) C300i: Black up to 225,000/1,000,000 pages (drum/developer) CMY up to 90,000/1,000,000 pages (drum/developer) C250i: Black up to 170,000/1,000,000 pages (drum/developer) CMY up to 65,000/1,000,000 pages (drum/developer)
Power consumption	220-240 V / 50/60 Hz; Less than 1.58 kW
System dimension (W x D x H)	615 x 688 x 918 mm (with DF-714)
System weight	Approx. 96.0 kg (with DF-714)

PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Print Speed A4 (mono/colour)	C360i - 36/36 ppm, C300i - 30/30 ppm, C250i - 25/25 ppm
Page description language	PCL6 (XL3.0); PCL5c; PostScript 3 (CPSI 3016); XPS
Operating System	Windows 7 (32/64); Windows 8/8.1 (32/64); Windows 10 (32/64)
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2;
	Windows Server 2016; Windows Server 2019;
	Macintosh OS X 10.10 or later; Unix; Linux; Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS); Mopria (Android);
	Konica Minolta Mobile Print (iOS/Android/Windows 10 Mobile);
	Mobile Authentication and Pairing (iOS/Android)
	Optional: Google Cloud Print; WiFi Direct

PRINTER SPECIFICATIONS (OPTIONAL)	
Print controller	Embedded Fiery IC-420
Controller CPU	AMD GX-424CC @ 2.4 GHz
Memory/HDD	2,048 MB / 500 GB
Page description language	Adobe PostScript 3 (CPSI 3020); PCL 6; PCL 5c

SCANNER SPECIFICATIONS

Scan speed (mono/colour)	Up to 100/100 ipm in simplex
	Up to 200/200 ipm in duplex
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV;
	Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF;
	XPS; Compact XPS; PPTX
	Optional: Searchable PDF; PDF/A 1a and 1b;
	Searchable DOCX/PPTX/XLSX
Scan destinations	2,100 (single + group); LDAP support

COPIER SPECIFICATIONS

Imaging technology	Laser
Toner technology	Simitri [®] HD polymerised toner
Copy/print speed A4 (mono/colour)	Up to 36/36 ppm
Copy/print speed A3 (mono/colour)	Up to 18/18 ppm
Autoduplex Speed A4 (mono/colour)	Up to 36/36 ppm
1 st copy out time A4 (mono/colour)	C360i - 4.6/6.1 sec, C300i - 5.0/6.7 sec, C250i - 5.2/6.9 sec
Warm-up time (mono/colour)	C360i - Approx. 12 sec. in mono; 13 sec. in colour ²
	C300i - Approx. 11 sec. in mono; 13 sec. in colour ²
	C250i - Approx. 11 sec. in mono; 13 sec. in colour ²
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	A6-A3; Custom sizes
Magnification	25–400% in 0.1% steps; Auto-zooming

FAX SPECIFICATIONS

Fax standard	Super G3 (optional)
Fax transmission	Analogue; i-Fax; Colour i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,100 (single + group)

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling
SYSTEM FEATURES	
Security Functions (standard)	ISO 15408 HCD-PP Common Criteria (in evalutation); IP filtering
	and port blocking; SSL2; SSL3 and TLS1.0/1.1/1.2 network
	communication; IPsec support; IEEE 802.1x support;
	User authentication; Authentication log; Secure print; Kerberos;
	SSD self-encrypting (AES 256), Memory data auto deletion;
	Confidential fax receipt; Print user data encryption
Security Functions (optional)	Antivirus realtime scanning (Bitdefender®);
	Copy protection (Copy Guard, Password Copy)
Accounting (standard)	Up to 1,000 user accounts; Active Directory support (user name
	password + e-mail + smb folder); User function access definition
Accounting Functions (optional)	ID card authentication (ID card reader);
	Authentication by mobile device (Android/iOS)
Software	PageScope Net Care Device Manager; PageScope Data Admin-
	istrator; PageScope Box Operator; PageScope Web Connection;
	Print Status Notifier; Driver Packaging Utility; Log Management
	Utility

¹ If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed ² Warm-up time may vary depending on the operating environment and usage

- All specifications refer to A4-size paper of 80 g/m² quality.
 The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations. The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
- particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.





Scope Business Imaging - Perth 80 Hasler Road, Osborne Park WA 6017

Ph. 08 9201 3000

info@scopebi.com.au scopebi.com.au

