



Product Code: 1579W  
 Product Series: Coated Glass Fabric



## Technical Data Sheet

### 1579W

<b>Style</b>	1579W
<b>Finish</b>	Silane
<b>Fiber Type</b>	Glass
<b>Weave Pattern</b>	Plain
<b>Density</b>	
<b>Warp Yarn</b>	G 150 1/2
<b>Fill Yarn</b>	G 75 1/0
<b>Breaking Strength</b>	0.15 ± 0.05 mm
<b>Count: Ends x Picks (per inch) Weight</b>	30 x 16
<b>Weight</b>	3.75 oz/yd <sup>2</sup> (127 ± 5 g/m <sup>2</sup> )
<b>Thickness (inch)</b>	0.15 ± 0.05 mm



VANDO INC-GRAPHITE MASTER  
 7436 Scout Ave.  
 Bell Gardens, CA 90201  
 (323) 261-1107  
[info@graphitemaster.com](mailto:info@graphitemaster.com)  
[www.graphitemaster.com](http://www.graphitemaster.com)

This information and data contained herein is offered solely as a guide in the selection of a reinforcement material. The information contained in this publication is based on actual laboratory data and field test experience. We believe this information to be reliable, but do not guarantee its applicability to the user's process. The user agrees to be responsible for thoroughly testing any application to determine its suitability before committing to production. The values listed for weight, thickness, and breaking strength are greige values, unless otherwise noted. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose.