




User's Manual



Installation Instructions For FreestandingTub Filler













CERTIFICATE OF LISTING

Kaiping Heart Cartridge Co., Ltd. No. 28 Meihuan Dong Road, Shuikou Town, Kaiping City, GUANDONG China







IAPMO RESEARCH AND TESTING, INC.









CERTIFICATE OF LISTING







IAPMO RESEARCH AND TESTING, INC.











CERTIFICATE OF LISTING




BEFORE INSTALLTION

Freestanding Bathtub Faucet Manual

1.Please check everything component by the list below after you open the package,make sure nothing missing,if any,please contact with the dealer where you buy from.


NO.	Part	PCS
1	Main Body	1
2	Straight Tube	1
3	Screw Driver	1
4	Screws	2
5	Decorative Cover	1
6	Inlet Tube	2
7	Bolts Holder	1
8	Expansion Bolts	3
9	Shower Head	1
10	Shower Tube	1
11	Manual	1




2. Using the faucet for a matching height bathtub.

INSTALL THE SHOWER

This product has been inspected and debugged by the factory to the best condition. Please do not disassemble and assemble it yourself.



Before installing the faucet, please be sure to remove sundries and sludge from the water pipe to prevent sundries from blocking the faucet.




1.Connect the straight tube, decorative tube and bolts holder to inlet tube then screw the inlet tube to main body




4. Connect the inlet tube like the drawing




7. Tighten the expansion bolts



2. Connect the main body with straight tube by screws, by using the screw driver provided.




5. Twist the bolts holder to the faucet




8. Twist the shower tube to both faucet and shower head




3. Prepare water inlet like the drawing below.



6.Drill holes on floor based




9. Finished assembly



CLEANING CARE

In order to keep the appearance of faucet clean, bright and good performance ,please take care of the faucet as follows;





- 2.Use mild liquid and colorless glass cleaner to remove surface dirt and scale film,or use polish without abrasive effect;
- 3.Do not use abrasive deterfgent, polish , emery cloth , paper towel or scraper , etc.;
- 4.Do not use acid cleaner, or cleaner and soap with insoluble gran etc.;
- 5.In the process of use ,mud my accumulate in the bubbler and make the water flow show, The bubbler can be unscrewed, rinsed with water ,and then installed back in place.

Please feel free to contact us if you have any questions. we will help to solve the issue together with you. OUR EMAIL: services@rbrohant.com





Service Contact:

6264872662 services@rbrohant.com

Made in China