IOMPAC'

DATASHEET V1.1

12.8V Lithium Battery LiFePO4

Model No: LPE-LFP12100-100

BATTERY FEATURES









KG







SPECIFICATIONS

ELECTRICAL SPECIFICATIONS					
Nominal Voltage	12.8V				
Nominal Capacity	100Ah				
Energy	1280Wh				
Internal Resistance	≤10 mΩ				
Efficiency	≥99%				
Self Discharge	<3% per month				

MECHANICAL SPECIFICATIONS				
Dimensions (LxWxH)	260x168x214mm			
Weight	9.9 kgs			
Cycles	≥3000 @ 80% DOD			
Case Material	ABS			
Enclosure Protection	IP65			
Terminal Type	M8 Internal Thread			
Cell Chemistry	LiFePO4			

SAFETY & PROTECTION SPECIFICATIONS				
Max Continuous Charge Current	100A Recommended (50A)			
Max Continuous Discharge Current	100A			
Peak Discharge	160A (10 Secs)			
Discharge Protection cut-off	10V			
Over Charge Protection cut-off	14.5V			
Passive Cell Balancing Voltage	3.5V			
Short Circuit Protection	600<500uS			

TEMPERATURE SPECIFICATIONS			
Storage Temperature	-10-45°C		
Discharge Temperature	-20-60°C		
Charge Temperature	0 - 60°C		

SAFETY INTSRUCTIONS

- Before use read & follow instructions provided by the manufacturer.
- Do not expose the battery to direct sunlight or extreme temperatures.
- Do not disassemble the battery. Opening the battery will VOID Warranty
- Do not short circuit the battery.
- Store the battery in a well ventilated area.
- Only use a recommended (LiFePO4) Lithium charger
- Do not immerse the battery in water.
- Do not crush, incinerate or modify the battery.
- Recycle the battery according to local regulations.

BATTERY CERTIFICATION









Here at LithiumPro Energy we pride ourselves on providing our customers with the very highest quality. All LithiumPro batteries have undergone rigorous testing procedures to ensure they comply fully with all UK & EU Legal Certification. Our batteries demonstrate compliance with UN38.8, UKCA, CE, ROHS, EMC & RED

Lithium Iron Phosphate is classified as a Class 9 Hazardous material so in order to ship the battery via Rail, Road or Sea they have to adhere stringent handling, packaging and labelling requirements of the United Nations UN38.3 Certification. If returning you will need to notify courier.

STORAGE

All Lithium Iron Phosphate batteries should be stored in a cool dry well ventilated environment. Avoid any exposure to direct sunlight or heat sources. If storing your Lithium Battery for an extended period it should be isolated from any loads and left at a storage charge level of between 50-80% to help prevent excessive self-discharge. LiFePO4 should be charged every 3 to 6 months to increase battery longevity.

CHARGING SPECIFICATIONS	12V	24V	36V	48V
Charging Voltage (CCCV)	14.4V	28.8V	43.2V	57.6V
Float Voltage	13.8V	27.6V	41.4V	55.2V
Recommended Charging Current	≤ 50A	≤ 50A	≤ 50A	≤ 50A
Parallel & Series Connections	Max 4 Connections			

WARRANTY

LithiumPro offers a 3 year warranty on CompactLite Battery. The Warranty will only apply to the original purchaser. Warranties are nontransferrable. LithiumPro Energy requires Proof of Purchase prior to processing any warranty claims or returns. We guarantee to repair or replace any unit that is determined to be defective in terms of manufacturing or technical defects. Our warranty does NOT cover damage resulting from customer negligence, misuse, abuse, accidental damage or general wear and tear.

