Slade Comp Hardtail | Trail | Alloy | 29"

€1.099,00

Hardtail trail and enduro riding is a sure-fire way to quickly boost your skill and confidence. Featuring our new sweet spot geometry, The Slade brings uncompromised climbing and descending prowess to trail hardtails. Tyre compatibility is 27.5x2.8"" or 29"" up to 2.6"" wide, giving plenty of setup options and creating our most versatile hardtail ever. 2.6"" Tyres are rapidly becoming the final word in trail tyres, offering noticeably improved comfort and grip over 2.3"" tyres, but without the weight, rolling resistance and thin carcasses of 2.8".





SPECIFICATIONS.

| Crankset | Prowheel Charm, 32t, External BB, Black |
|-----------------|--|
| Cassette | Shimano HG-50-10 10 Speed 11-42t |
| Rear Der | Shimano Deore M6000, Medium Cage, Black |
| Shifters | Shimano Deore 10 Speed, Black |
| Fork | SR Suntour XCM34 Boost LO, 130mm, Black, Boost 110 |
| Hubs | Front Hub: Promax Sealed Cartridge, 110x15, 6 Bolt, Rear Hub: Promax Sealed Cartridge, 148x12, 6 Bolt |
| Rims | SUNringle Duroc 35, STR Tubeless, 32mm Internal Width |
| Tyres | Vee Rubber Flow Snap 29x2.6" |
| Seatpost | X-Fusion Manic Dropper Post, Internal Routing L: Drop:125 for size S, L: Drop:150 for size M, L: Drop:150 for size L, L: Drop:150 for size XL |
| Saddle | Sector Ergo, Black Steel Rails |
| Handlebar | Sector Alloy Handlebar, Dia:31.8mm, Backsweep:9°, Rise 5mm; W: 780 for size S, W: 780 for size M, W: 780 for size L, W: 780 for size XL |
| Stem | Sector Alloy Stem, 31.8mm, Rise 6°, with stainless steel bolts; L: 45 for size S, L: 45 for size M, L: 45 for size L, L: 45 for size XL |
| Frame | 29" Butted 6061 Aluminium, Tapered 1- 1/8"-1.5" Headtube, 12 x 148mm, SBC 12mm Thru Axle Dropouts |
| Brake set | Shimano M315 Hydraulic Disc Brakes, Resin Pads, Rotors: Shimano SM-RT26 180mm/160mm, 6 Bolt |
| Weight | 14.95kg (Medium Frame, with tubes, without pedals) |
| Weight Limit | 120kg - combined weight of bike and rider (including all kit). |
| Travel | F: 130mm |
| | |