

Slade Trail

Hardtail | Trail | Alloy | 29"

€1.461,00

Slade is unlike any hardtail you've ridden before. Featuring our sweet spot geometry - POP - to bring uncompromised climbing and descending prowess to trail bikes. POP engages bigger muscle groups for more efficient climbing and the rider position on the bike improves traction and cornering grip. Tyre compatibility is 27.5x2.8" or 29" up to 2.6" wide, giving plenty of setup options and creating our most versatile hardtail ever. 2.6" Tyres are rapidly becoming the final word in trail tyres, offering noticeably improved comfort and grip over 2.3" tyres, but without the weight, rolling resistance and thin carcasses of 2.8".



SPECIFICATIONS.

Crankset	Raceface Ride, 32t, Black
Cassette	Sunrace 11-46 11 Speed, 418% Wide Range
Rear Der	Shimano XT M8000 Long Cage, Black
Shifters	Shimano SLX M7000 11 Speed, Black
Fork	Rockshox Revelation RC Motion Control, 140mm , Diffusion Black, Boost 110, Reduced 42mm Offset
Hubs	Front Hub: Promax Sealed Cartridge, 110x15, 6 Bolt, Rear Hub: Promax Sealed Cartridge, 148x12, 6 Bolt
Rims	Stan's Flow S1, 29mm Internal Width
Tyres	Maxxis Rekon 29x2.6", EXO/TR, 60Tpi
Seatpost	X-Fusion Manic Dropper Post, Internal Routing L: Drop:125 for size S, L: Drop:150 for size M, L: Drop:150 for size L, L: Drop:150 for size XL
Saddle	Sector Ergo, Black Steel Rails
Handlebar	Sector Alloy Handlebar, Dia:31.8mm, Backsweep:9°, Rise 5mm; W: 780 for size S, W: 780 for size M, W: 780 for size L, W: 780 for size XL
Stem	Sector Alloy Stem, 31.8mm, Rise 6°, with stainless steel bolts; L: 45 for size S, L: 45 for size M, L: 45 for size L, L: 45 for size XL
Frame	29" Butted 6061 Aluminium, Tapered 1-1/8"-1.5" Headtube, 12 x 148mm, SBC 12mm Thru Axle Dropouts
Brake set	Shimano MT500 Hydraulic Disc Brakes, Resin Pads, Rotors: Shimano SM-RT26 180mm/160mm, 6 Bolt
Weight	12.96kg (Medium Frame, with tubes, without pedals)
Weight Limit	120kg - combined weight of bike and rider (including all kit).
Travel	F:140mm