	Alpha / Alpha S		
COMPONENT	SPECIFICATION	MATERIAL	COLOR
- rame	Vvolt Alloy w/Removable Downtube Battery, fender, rack and 1x bottle cage mounts	Alloy	Painted
Fork	Vvolt Alloy Thru Axle w/ 3-pack fender and accessory mounts	Alloy	Painted
lead Set	Integrated sealed bearing	Alloy	Black
landlebar	Alloy 31.8, 20mm rise x 660mm width	Alloy	Black
item	31.8 Clamp, 7º rise	Alloy	Black
1otor / Rear Hub	Xplova, 350w nominal power, 45nm max torque	Alloy/Steel	Black
Computer	Xplova - LED Display w/ USB charging port		
-Power Battery	36V 10.4Ah Integrated Battery 375Wh LG Cells	Lithium	Black
-Power Charger	e-Bike Battery Charger 36V2AP, 100-240V Output 36V/2A		
Crankset	Gates S100 Square Taper, 170mm, 5x130mm BCD	Steel/Alloy	Black
ottom Bracket	Cadence Sensor Sealed Bearing Square Taper, 68mmx116	Steel	Ni-plated
elt Drive Sprocket	Gates CDN, 50t	Alloy	Black
Belt Drive Freewheel	Gates 22t	Steel	Silver
Prive Belt	Gates CDN, 118t	Carbon	Black
Brakes	CStar Radius Hydraulic, 160mm rotors	Alloy	Black
ront Hub	Sealed Bearing, 15x100mm Thru-Axle Disc, 32h	Alloy	Black
pokes	black steel 14g front, 12g rear	UCP	Black
lipples	Brass	Brass	Black
lims	Black Alloy, Disc Specific 32h front 36h rear	Alloy	BK/CNC
ires	27.5 x 1.95, low tread pattern for street and gravel	Rubber	Black
edals	Plastic platform w/reflectors	Resin	Black
addle	Hybrid Gel Comfort Saddle	Steel	Black
eat Post	27.2 x 350mm	Alloy	Sand Black
eat Clamp	Bolt-On	Alloy	Black
Frips	Ergonomic Shape Dual-Density	Rubber	Black
ickstand	Black, rear-mounted w/Adjustable foot	Alloy/Plastic	
ell	Mini Bell	Steel	Black