





GT3 - Factory setup sheet - **Hankook**

Note: When carrying out set-up on flat-patch, set tyre pressures to hot pressure. Ensure that they are returned to cold pressures after setup is complete.

Date		Chassis #		Job #	
		Technician 1		Technician 2	

Camber		
-2.5	↑	-2.5
-2.0		-2.0

Toes		
2mm OUT	↑	2mm OUT
3mm IN		3mm IN



Triple Intrax		Springs/Preload			Triple Intrax	
Bump LS:	-7	Rate	FARB	Rate	Bump LS:	-7
Bump HS:	-25	180	22.2mm	180	Bump HS:	-25
Rebound:	-25		25.4mm		Rebound:	-25
		Length	28.6mm	Length		
		130mm	↑	130mm		
		Preload		Preload		
		8mm		8mm		

Ride	Front Diffuser H	Ride
82mm	42mm	82mm
	Ballast Weight	
	85kg	
Drop	Cross%	Drop
297mm		297mm
Weight	Total weight	Weight
kg	kg	kg

Triple Intrax		Springs/Preload			Triple Intrax	
Bump LS:	-7	Rate	RARB	Rate	Bump LS:	-7
Bump HS:	-25	160	15.9mm	160	Bump HS:	-25
Rebound:	-25		19.1mm		Rebound:	-25
		Length	22.2mm	Length		
		130mm	25.0mm	130mm		
		Preload		Preload		
		0mm		0mm		

Ride	Rake mm	Ride	
108mm	22mm	108mm	
	↑		
Drop		Drop	
224mm		224mm	
Weight	LHD	RHD	Weight
kg			kg

Wheel Size
Front
18"x10.5"
Rear
18"x11.5"

BOP Ballast
Fuel Level
5L

Dive planes: Y / N

Tyre Pressure (PSI) (Cold & Hot)		
28	Hankook	28
20	↑	20
28		28
19		19

PADS
01
PADS
01

Rear Wing	
Holes (from the bottom)	
Main	3 out of 4
Bi-wing	7 out of 11

Comments:

