

## ULTRA R5000 LASER SYSTEM

---

The ULTRA R5000 offers a 32 in x 24 in (813 mm x 610 mm) material processing area.

It can be configured in a CO<sub>2</sub> only configuration (10.6 or 9.3 μm) or a multiple wavelength configuration (CO<sub>2</sub> and fiber). A maximum of 150 watts of laser power is supported in a CO<sub>2</sub> only configuration. A maximum of 150 watts CO<sub>2</sub> and 50 watts fiber is supported in a multiple wavelength configuration.



ULTRA R5000

### KEY FEATURES AND CAPABILITIES

- Supports two lasers – (2) CO<sub>2</sub> sources or (1) CO<sub>2</sub> and (1) fiber laser source
- Patented Multi-Wave Hybrid™ technology
- Supports material thickness up to 12 in (305 mm)
- Precision Material Independent Autofocus
- Patent pending Controllable Laser Power Density Optics
- Programmable Gas Assist
- Laser System Manager control software
- Intelligent Materials Database
- Rapid Reconfiguration™ technology

#### *Configuration Components Available*

- Multi-Camera Vision and Registration
- Patented SuperSpeed™ technology
- 21 in (533 mm) Touch Screen Control Panel
- Fire Suppression
- Automation Interface
- UAC 4000 Air Filtration

## SPECIFICATIONS

<b>Material Processing Envelope (X,Y,Z)</b>	32 x 24 x 12 in. (813 x 610 x 305 mm)
<b>Maximum Effective Raster Processing Speed</b>	Equivalent to more than 200 in./sec (equivalent to more than 5080 mm/sec) - Requires SuperSpeed configuration
<b>Multiple Laser Support / Maximum Laser Power</b>	Up to 150 watts with (2) 75 watt CO <sub>2</sub> laser sources or (1) 150 watt CO <sub>2</sub> laser source; Up to 150 watts CO <sub>2</sub> and 50 watts fiber in a multiple wavelength configuration; <i>Supports Rapid Reconfiguration™ of CO<sub>2</sub> lasers</i>
<b>Wavelengths / Laser Sources Available</b>	10.6 μm CO <sub>2</sub> : 10, 30, 40, 50, 60, 75 and 150 watt laser sources 9.3 μm CO <sub>2</sub> : 10, 30, 50 and 75 watt laser sources 1.06 μm Fiber: 50 watt laser source
<b>System External Dimensions</b>	Width: 55.00 in. (1397 mm) without Control Panel Depth: 46.32 in. (1177 mm) Height: 48.00 in. (1219 mm) to top of enclosure e-stop
<b>Computer Requirements</b>	Minimum: Intel i3 processor (or equivalent) with at least 8 GB of memory, Windows 10 operating system and connection to laser system with USB cable; <i>Not required if configured with available 21" Touch Screen Control Panel</i>
<b>Laser Safety Classification</b>	Class 1 for material processing lasers; Class 2 overall due to red laser pointer; Can convert to Class 4 with optional Class 4 module

\*Full specifications are available on the ULS website and are subject to change

WARNING: UNIVERSAL LASER SYSTEMS PRODUCTS ARE NOT DESIGNED, TESTED, INTENDED OR AUTHORIZED FOR USE IN ANY MEDICAL APPLICATIONS, SURGICAL APPLICATIONS, MEDICAL DEVICE MANUFACTURING, OR ANY SIMILAR PROCEDURE OR PROCESS REQUIRING APPROVAL, TESTING, OR CERTIFICATION BY THE UNITED STATES FOOD AND DRUG ADMINISTRATION OR OTHER SIMILAR GOVERNMENTAL ENTITIES. FOR FURTHER INFORMATION REGARDING THIS WARNING CONTACT UNIVERSAL LASER SYSTEMS OR VISIT WWW.ULSINC.COM.



Universal laser systems are protected under one or more U.S. Patents: 7,060,934; 7,415,051; 7,715,454; 7,723,638; 7,947,919; 8,101,883; 8,294,062; 8,599,898; 8,603,217; 9,155,988; 9,263,844; 9,263,845; 9,281,649; 9,346,122; 9,354,630; 9,694,448; 9,737,958; 10,391,345; 10,456,875; 11,198,193. Other U.S. and international patents pending.

© 2023 Universal Laser Systems, Inc. All rights reserved. Universal Laser Systems logo and name are registered trademarks of Universal Laser Systems, Inc. All other company and product names are trademarks or registered trademarks of their respective companies.

**Abernethy Beck, INC.**

704-527-5968 – info@abernethybeck.com  
PO Box 472808, Charlotte, NC 28247 USA