

ULTRA R9000 LASER SYSTEM

The ULTRA R9000 is the largest laser system in the ULTRA series with a 48 in x 24 in (1219 mm x 610 mm) material processing area.

The ULTRA R9000 can be configured in a CO_2 only configuration (10.6 or 9.3 μ m) or a multiple wavelength configuration (CO_2 and fiber). A maximum of 300 watts of laser power is supported in a CO_2 only configuration. A maximum of 150 watts CO_2 and 50 watts fiber is supported in a multiple wavelength configuration.



ULTRA R9000

KEY FEATURES AND CAPABILITIES

- Supports two lasers (2) CO₂ sources or
 (1) CO₂ and (1) fiber laser source
- Patented Multi-Wave Hybrid™ technology
- Supports material thickness up to 12 in (305 mm)
- Precision Material Independent Autofocus
- Patent pending Controllable Laser Power Density Optics
- Programmable Gas Assist

- Laser System Manager control software
- Intelligent Materials Database
- Rapid Reconfiguration[™] technology

Configuration Components Available

- Multi-Camera Vision and Registration
- Patented SuperSpeed[™] technology
- 21 in (533 mm) Touch Screen Control Panel
- Fire Suppression
- Automation Interface
- UAC 4000 Air Filtration



SPECIFICATIONS	
Material Processing Envelope (X,Y,Z)	48 x 24 x 12 in. (1219 x 610 x 305 mm)
Maximum Effective Raster Processing Speed	Equivalent to more than 200 in./sec (equivalent to more than 5080 mm/sec) - Requires SuperSpeed configuration
Multiple Laser Support / Maximum Laser Power	Up to 300 watts with (2) CO_2 laser sources; Up to 150 watts CO_2 and 50 watts fiber in a multiple wavelength configuration; Supports Rapid Reconfiguration [™] of CO_2 lasers
Wavelengths / Laser Sources Available	$10.6~\mu m$ CO_2 : $10,30,40,50,60,75$ and 150 watt laser sources $9.3~\mu m$ CO_2 : $10,30,50$ and 75 watt laser sources $1.06~\mu m$ Fiber: 50 watt laser source
System External Dimensions	Width: 71.00 in. (1803 mm) without Control Panel Depth: 46.32 in. (1177 mm) Height: 48.00 in. (1219 mm) to top of enclosure e-stop
Computer Requirements	Minimum: Intel i3 processor (or equivalent) with at least 8 GB of memory, Windows 10 operating system and connection to laser system with USB cable; Not required if configured with available 21" Touch Screen Control Panel
Laser Safety Classification	Class 1 for material processing lasers; Class 2 overall due to red laser pointer; Can convert to Class 4 with optional Class 4 module

^{*}Full specifications are available on the ULS website and are subject to change.

WARNING: UNIVERSAL LASER SYSTEMS PRODUCTS ARE NOT DESIGNED, TESTED, INTENDED OR AUTHORIZED FOR USE IN ANY MEDICAL APPLICATIONS, SURGICAL APPLICATIONS, MEDICAL DEVICE MANUFACTURING, OR ANY SIMILAR PROCEDURE OR PROCESS REQUIRING APPROVAL, TESTING, OR CERTIFICATION BY THE UNITED STATES FOOD AND DRUG ADMINISTRATION OR OTHER SIMILAR GOVERNMENTAL ENTITIES. FOR FURTHER INFORMATION REGARDING THIS WARNING CONTACT UNIVERSAL LASER SYSTEMS OR VISIT WWW.ULSINC.COM.



Universal laser systems are protected under one or more U.S. Patents: 7,060,934; 7,415,051; 7,715,454; 7,723,638; 7,947,919; 8,101,883; 8,294,062; 8,599,898; 8,603,217; 9,155,988; 9,263,844; 9,263,845; 9,281,649; 9,346,122; 9,354,630; 9,694,448; 9,737,958; 10,391,345; 10,456,875; 11,198,193. Other U.S. and international patents pending.

© 2023 Universal Laser Systems, Inc. All rights reserved. Universal Laser Systems logo and name are registered trademarks of Universal Laser Systems, Inc. All other company and product names are trademarks or registered trademarks of their respective companies.

UNIVERSAL LASER SYSTEMS, INC.
GLOBAL HEADQUARTERS —
7845 E PARADISE LN, SCOTTSDALE, AZ 85260, USA
www.ulsinc.com

INTERNATIONAL OFFICES IN AUSTRIA AND JAPAN WORLDWIDE SALES, SERVICE, AND SUPPORT