



SAFETY DATA SHEET

Screen Print Essentials Limited - Flashcure Textile Adhesive 600ml Aerosols

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Screen Print Essentials Limited - Flashcure Textile Adhesive 600ml Aerosols
Product number 3042

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Screen Print Essentials Ltd
 20 Rowes Yard
 Manston Business Park
 Kent
 CT12 5FA
 Tel: 03300 553640
 info@spe-online.co.uk

1.4. Emergency telephone number

Emergency telephone 03300 553640 (Hours 08:00 - 17:00 Mon to Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229
Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336
Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) F+; R12. Xi; R38. R52/53, R67


Human health Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards.

Environmental The product contains a substance which is harmful to aquatic organisms.

Physicochemical Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is extremely flammable. Vapours may form explosive mixtures with air.

2.2. Label elements

Pictogram



Signal word Danger

Screen Print Essentials Limited - Flashcure Textile Adhesive 600ml Aerosols

Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Contains	HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE, HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE
Supplementary precautionary statements	P264 Wash contaminated skin thoroughly after handling. P273 Avoid release to the environment. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTRE/doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE	30-60%
CAS number: 68476-85-7	EC number: 270-704-2
Classification	
Flam. Gas 1 - H220	
Press. Gas (Comp.) - H280	
DIMETHOXYMETHANE	10-30%
CAS number: 109-87-5	EC number: 203-714-2
	REACH registration number: 01-2119664781-31-XXXX
Classification	
Flam. Liq. 2 - H225	

Screen Print Essentials Limited - Flashcure Textile Adhesive 600ml Aerosols

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during firefighting Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

Advice on general occupational hygiene Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

DIMETHOXYMETHANE

Screen Print Essentials Limited - Flashcure Textile Adhesive 600ml Aerosols

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 3160 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 3950 mg/m³

WEL = Workplace Exposure Limit

DIMETHOXYMETHANE (CAS: 109-87-5)

DNEL	Workers - Dermal; Long term systemic effects: 22 mg/kg/day Workers - Inhalation; Long term systemic effects: 132 mg/m ³ General population - Oral; Long term systemic effects: 9.6 mg/kg/day General population - Inhalation; Long term systemic effects: 39 mg/m ³ General population - Dermal; Long term systemic effects: 5.7 mg/kg/day
PNEC	- Fresh water; 14577 mg/l - Marine water; 14577 mg/l - Sediment (Freshwater); 13135 mg/kg/day - Sediment (Marinewater); 13135 mg/kg/day - Soil; 46538 mg/kg/day - STP; 10000 mg/l

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

DNEL	Consumer - Oral; Long term systemic effects: 699 mg/kg/day Workers - Oral; Long term systemic effects: 773 mg/kg/day Workers - Dermal; Long term systemic effects: 773 mg/kg/day Consumer - Dermal; Long term systemic effects: 699 mg/kg/day Consumer - Inhalation; Long term systemic effects: 608 mg/m ³
-------------	--

HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE (CAS: 64742-49-0)

DNEL	Consumer - Oral; Long term systemic effects: 1301 mg/kg/day Consumer - Dermal; Long term systemic effects: 1377 mg/kg/day Workers - Dermal; Long term systemic effects: 13964 mg/kg/day Consumer - Inhalation; Long term systemic effects: 1131 mg/m ³ Workers - Inhalation; Long term systemic effects: 5306 mg/m ³
-------------	--

8.2. Exposure controls

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
Hand protection	No specific requirements are anticipated under normal conditions of use.
Other skin and body protection	Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.
Respiratory protection	No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Off-white.
Odour	Solvent.
Odour threshold	No information available.
pH	No information available.

Screen Print Essentials Limited - Flashcure Textile Adhesive 600ml Aerosols

Melting point	No information available.
Initial boiling point and range	-41 (-41 TO 95)°C @
Flash point	-40°C Closed cup.
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.0 % Upper flammable/explosive limit: 19.9 %
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	0.680
Solubility(ies)	Insoluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	237°C
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Oxidising properties	No information available.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability The product may not be stable under some conditions of storage or use.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid None known.

10.6. Hazardous decomposition products

Hazardous decomposition products None at ambient temperatures.

SECTION 11: Toxicological information

Screen Print Essentials Limited - Flashcure Textile Adhesive 600ml Aerosols

11.1. Information on toxicological effects

Inhalation	Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.
Skin contact	Causes skin irritation.
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.
Acute and chronic health hazards	No specific long-term effects known.
Route of exposure	Inhalation Dermal

Toxicological information on ingredients.

DIMETHOXYMETHANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 6,950.0

Species Rat

ATE oral (mg/kg) 6,950.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,001.0

Species Rabbit

ATE dermal (mg/kg) 5,001.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 15,000.0

Species Rat

ATE inhalation (vapours mg/l) 15,000.0

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,001.0

Species Rat

ATE oral (mg/kg) 5,001.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,001.0

Species Rabbit

ATE dermal (mg/kg) 2,001.0

Screen Print Essentials Limited - Flashcure Textile Adhesive 600ml Aerosols

HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,001.0

Species Rat

ATE oral (mg/kg) 5,001.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,001.0

Species Rabbit

ATE dermal (mg/kg) 2,001.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 21.0

Species Rat

ATE inhalation (vapours mg/l) 21.0

SECTION 12: Ecological Information

12.1. Toxicity

Ecological information on ingredients.

DIMETHOXYMETHANE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 1001 mg/l, Fish

Acute toxicity - aquatic invertebrates LC₅₀, 48 hours: 1201 mg/l, Daphnia magna

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

Acute aquatic toxicity

Acute toxicity - fish LOEC, : 1-10 mg/l, Fish

Acute toxicity - aquatic plants LOEC, : 10-100 mg/l, Algae

Acute toxicity - microorganisms LOEC, : 1-10 mg/l, Activated sludge

HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE

Acute aquatic toxicity

Acute toxicity - fish LOEC, : 10-100 mg/l, Fish

Acute toxicity - aquatic plants LOEC, : 10-100 mg/l, Algae

12.2. Persistence and degradability

Screen Print Essentials Limited - Flashcure Textile Adhesive 600ml Aerosols

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Partition coefficient No information available.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Disposal methods Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.

Waste class The waste code classification is to be carried out according to the European Waste Catalogue (EWC).

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS, FLAMMABLE

Proper shipping name (IMDG) AEROSOLS, FLAMMABLE

Proper shipping name (ICAO) AEROSOLS, FLAMMABLE

Proper shipping name (ADN) AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Screen Print Essentials Limited - Flashcure Textile Adhesive 600ml Aerosols

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended). Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	04/07/2018
Revision	2
Supersedes date	13/06/2014
SDS number	7561

Screen Print Essentials Limited - Flashcure Textile Adhesive 600ml Aerosols

Hazard statements in full	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.
----------------------------------	---

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.