Eco-Strip®A

(APEO / NPEO FREE)

Multi-Purpose Screen Wash

GENERAL DESCRIPTION

Eco-Strip®A is water soluble ink degradent. It is highly effective on plastisol, multipurpose (solvent based), and UV inks. Eco-Strip®A can also be diluted with water. This makes it ideal for use with water-base ink systems. Eco-Strip®A will protect the fabric from deep stains or ghosting from the image print. This makes it much easier when complete reclamation of the

Eco-Strip®A can be used in a wide variety of innovative cleaning processes ranging from re-circulation machines, dip tanks, immersion cleaning processes, and automatic reclaiming machines. It can also be applied manually with a scrub pad, spary bottle, or pneumatic pump systems.


Eco-Strip®A is also an excellent plastisol ink haze (ghost) remover. It is non hazardous (noncorrosive) and aggressively removes image stains from the mesh.

ADVANTAGES

- Easy to use
- · Economical Can be diluted with water
- · Reduces labor
- Low Odor
- · Low Foam
- · Low-VOC (volatile organic compounds) : after dilution with water
- · High Solvency: immediatley breaks down ink
- · High Flash Point / Non-Flammable
- · Non-Hazardous
- · High load capacity to reduce usage
- · Safe on all types of mesh
- · Biodegradable / Drain Safe
- · Ideal for use in automatic reclaiming equipment
- Multiple applications
- · Does NOT Contain Alkylphenol Ethoxylates (APEO) / Nonylphenol Ethoxylates (NPEO)

APPLICATIONS

Always card excessive ink from screen. Use one of the following applications.



Card excessive ink from the screen. Apply Eco-Strip® A to ink side of screen. Use a non-abrasive scrub brush or pad to agitate ink on both sides of screen. Finally, rinse away all residue away using high pressure

Haze Remover:

After ink and emulsion has been removed, spray Eco-Strip® A on both sides of the screen. Scrub screen both sides with a non-abrasive brush or pad. Allow product to dwell a few minutes (depending on severity of stain). High pressure rinse screen working from bottom and moving upwards.

> **SQ-1000** Squeegee Cleaner Click here for more details.

RECIRCULATING WASH:

Card excessive ink from the screen. This product can be continuously recirculated until product becomes too heavily soiled with solids. Used product may be filtered and reused.

Packaging

5 gallon pail 1 gallon 55 gallon drum Quick Tip:

Always pressure wash screen from the bottom and work upwards.

This will prevent ink from locking back onto the mesh when coming in contact with the rinse water.

