

Wine-Mate 4500SSVWC Split Rack- Recessed Wine Cooling System

Wine-Mate rack split cooling systems WM-2500~6500SSVWC are designed and used to provide a cold temperature between 50~65 °F for a properly insulated wine cellar. The wine cellar will maintain humidity range within 50~75% RH. These temperature and humidity ranges like in natural caves are optimized for long term storage of wine. SSVWC units consist of a condensing unit and an evaporator unit; they are connected by a liquid line and an insulated suction line. SSVWC condensing units can be located away from the evaporator unit 75 ft so that noise and compressor vibration are isolated. SSVWC condensing units are water cooled so that exhaust ventilation is not needed. SSVWC evaporator units are designed for installation inside a rack or in a wine room corner, making them an ideal choice for small and medium wine cellars. There are also multiple air inlet and outlet doors for different installations.



Key Features

- Stable temperature between 50~65 °F for a properly insulated room in a normal environment
- Maintain humidity of 50~75% RH even when the environment becomes dry or humid
- The condensing unit can be placed up to 75 feet away from the wine room, which will allow for extremely quiet operation
- The evaporator unit is designed for installation in a wine rack or inside a wine room corner
- If placing in a void corner, removable racking will be required to allow for access to unit
- Perfect for storing cigars, chocolate, salami, and fine leather and furs (additional cost and customization required)

Specifications

| | |
|-----------------|--|
| Cellar Size: | 1000 cu ft |
| Btu/h, CFM: | 4500 Btu/h, 335 CFM |
| Decibel Rating: | 56 dBA |
| Dimensions: | Evaporator: 11-3/8"W x 11-3/16"D x 47-1/2"H Condenser: 24"W x 18"D x 18"H |
| Electrical: | Evaporator: 115V/60Hz/1A Condenser: 115V/60Hz/6A |
| Weight: | Evaporator: 55 lbs Condenser: 60 lbs |
| Refrigerant: | R134a |
| Thermostat: | Advanced Digital Control Display |