

INSTALLATION STEPS

★ Turn off power each time before switch color temperature

Step 1: Toggle the switch on junction box to the correct place. Toggle it to the leftmost, CCT is 3000K,

Toggle it to the middle, it's 5000K; Toggle it to the rightmost, it's 4000K. Default set is 3000K.

Step 2: Cut hole on ceiling based on above cut out size (4" : 4" ~ 4 1/4" (100 - 108mm) 6" : 6"(152mm)).








Step 3: Open cover of junction box, then push and remove one of the half-inch knockouts on the side.

Step 4: Install standard L16 cable connector. Insert same color wires to the corresponding push in connectors that on the driver's "L" "N" "E" wires. Then close the junction box cover.

Step 5: Connect driver to LED fixture by tighten the male and female connector with hand.

Step 6: Locate the junction box beside the fixture above the ceiling.

Step 7: Snap fixture in the opening hole with spring clips.



INSTALLATION INSTRUCTIONS FOR COLOR TEMPERATURE CHANGEABLE LED SLIM PANEL LIGHT FIXTURE

★ Turn off power each time before switch color temperature

Please read carefully instructions before installation.

CAUTION: Turn off power at fuse or circuit breaker box before installation and maintenance. Fixture must be installed according to Local Electric Code and Local Building Code. Installation must be handled by a qualified licensed electrician understanding all electrical requirements involved.

WARNING: Avoid fire or electrical shock: ALWAYS disconnect/terminate power to a fixture prior to installation or replacement. Failure to do so may result in shock and/or serious injury. The operating voltage of this product is 110-120V. An installer must verify operating voltage of the fixture prior to installation.

Do not expose direct to water, it is not waterproof. Only suitable for dry and damp location.

Do not connect slim panel to any other driver except the one packed together.

Do not connect multiple slim panel to one driver and don't disassemble slim panel light.

FEATURES

* LED Driver and fixture are both IC rated - approved for direct contact with insulation.

* cETLus approved, CONFORMS TO UL STD. 1598. CERTIFIED TO CSA STD. C22.2 No. 250.0.

* Driver Input Voltage: 120VAC (Dimmable), Output Voltage : 36VDC.

* Operating Temperature: -40° F to + 104° F / -40 °C to + 40°C .

DIMENSIONS

ROUND 4" SLIM PANEL: Dia:4 4/5" (120mm) Height: 1/2" (13mm) Cut Out: 4" ~ 4 1/4" (100 - 108mm)

ROUND 6" SLIM PANEL: Dia: 6 4/5"(174mm) Height: 1/2" (13mm) Cut Out: 6"(152mm)

DIMMING

Compatible with Triac Base Dimmers.