

SR-2819S-CCT (R2)

CCT Remote Controller

Model No.:	SR-2819S-CCT (R2)	
Output:	RF Signal	
Voltage:	4.5V (3xAAA battery)	
Frequency:	434MHz/869.5MHz/916.5MHz	
Control Zone:	4 Zone	
Color Controller:	CCT	
Compatible Controllers:	SR-1009EATYWI-5C (R-8A) SR-1009EA-5C (R-25.5A) SR-1009TYWI-5C (R-4A)	
Operating Temperature:	0-40° C	
Relative Humidity:	8% to 80%	
IP Rated:	IP20 (Indoor use only)	
Dimensions:	120mm x 55mm x 17mm (4.725" x 2.17" x 0.67")	
Certifications:	CE/FCC/RoHS	

Name:		
Compar	ıy:	
Phone:		
Email:_		



Features:

- · LED remote controller for CCT color temperature lighting fixtures.
- . Operates on RF signal with frequency options of 434MHz, 869.5MHz, or 916.5MHz.
- Requires 3 AAA batteries with 4.5V voltage for power.
- 4-zone control capability and functions as a dimmer for the lighting fixtures.
- Black in color with operating temperature range of 0-40°C and relative humidity range of 8% to 80%.
- IP20 rating protects against solid objects >12mm in size, but no protection against water.
- Allows users to adjust color temperature for desired ambiance and lighting effect.







Disclaimer:

The data and information contained in this specification sheet are subject to change without notice; the ratings supplied are provided based on the product manufacturer. The information contained in this specification sheet should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose. In no event shall Veroboard be liable for any incidental or consequential damages resulting from the use, misuse, or inability to use the product. This exclusion applies regardless of whether such damages are sought based on breach of warranty, breach of contract, negligence, strict liability in tort, or any other legal theory.

