

SR-2819S (R3) RGBW Remote Controller

Model No.:	SR-2819S (R3)
Output:	RF Signal
Voltage:	4.5V (3xAAA battery)
Frequency:	434MHz/869.5MHz/916.5MHz
Control Zone:	4 Zone
Color Controller:	RGBW
Compatible Controllers:	SR-1009EATYWI-5C (R-8A) SR-1009EA-5C (R-25.5A) SR-1009TYWI-5C (R-4A)
Operating Temperature:	0-40° C
Relative Humidity:	8% to 80%
IP Rated:	IP20 (Indoor use only)
Dimensions:	120mm x 55mm x 17mm (4.725" x 2.17" x 0.67")
Certifications:	CE/FCC/RoHS

Name: _____

Company: _____

Phone: _____

Email: _____



Features:

- User-friendly interface, easy and simple operation.
- Operation return function
- Control up to 4 zones, each zone can be set endless receivers, each receiver maximally be controlled by 8 different remotes
- Set 3 scenes for each zone.
- Operation return function on this Remote RF LED remote.
- Preset 10 changing modes, with pause function.
- Synchronization function of pattern changes ensure consistent change forever.
- Enable to dim brightness of each R, G, B, W channel, in order to mix millions colors.



Disclaimer:

The data and information contained in this specification sheet are subject to change without notice; the ratings supplied are provided based on the product manufacturer. The information contained in this specification sheet should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose. In no event shall Veroboard be liable for any incidental or consequential damages resulting from the use, misuse, or inability to use the product. This exclusion applies regardless of whether such damages are sought based on breach of warranty, breach of contract, negligence, strict liability in tort, or any other legal theory.

