

SIZING CHART

STANDARD SIZING



See Sizing Chart below for Larger Deck Jacks: Standard size Jack Plus Extensions

<p>SOLD AS: SE6 140-233mm</p>  <p>SE3 75-120mm</p>	<p>SOLD AS: SE7 185-275mm</p>  <p>SE4 120-170mm</p>	<p>SOLD AS: SE8 235-325mm</p>  <p>SE5 170-215mm</p>
<p>SOLD AS: SE9 205-345mm</p>  <p>SE3 75-120mm</p>	<p>SOLD AS: SE10 250-385mm</p>  <p>SE4 120-170mm</p>	<p>SOLD AS: SE11 300-400mm</p>  <p>SE5 170-215mm</p>
<p>SOLD AS: SE12 270-455mm</p>  <p>SE3 75-120mm</p>	<p>SOLD AS: SE13 315-500mm</p>  <p>SE4 120-170mm</p>	<p>SOLD AS: SE14 365-555mm</p>  <p>SE5 170-215mm</p>

Extensions are NOT sold separately



STAR.T
8-15mm

Nurajack Star.T

The smallest Nurajack is the Nurajack Star.T. Starting at a height of 8mm, the Nurajack Star.T can be adjusted up to 15mm.

The Nurajack Star.T is leveled using a Nurajack Shim (available in 1mm, 2mm or 3mm)

It may be that the installer is satisfied with the tiles following the fall of the membrane, in which case no leveling of the Nurajack Star.T is required.



STAR.B
0-5mm

Nurajack Star.B

The Nurajack Star.B is a 5mm base for the Nurajack Star.T. The Nurajack Star.B bases can be stacked under the Nurajack Star.T up to 3 high, giving the Nurajack Star.T and Star.B combination an adjustable size of between 8mm to 30mm.



SHIM 1,2,3.

Shim

The Nurajack Shim is designed for use with the Nurajack and Nurajack. The Shim can be used to accommodate any variance in thickness of pavers or tiles. They can also be used to level a Nurajack or Nurajack Star.T if necessary.



TILE CLADDING SPACER

Tile Cladding Spacer

Under the building code a space must be maintained between the installed tiles and the wall, cladding, joinery or balustrade. Nuralite's Tile Cladding Spacers are a self-adhesive rubber bumper available in 5mm, 10mm and 14mm sizes and maintain the space required. Each Tile Cladding Spacer is slightly compressible and needs to be compressed in place during installation.



Nurajack Mini Spacer (NJMS)

The Nurajack Mini Spacer is designed for installing 20mm tiles/structural pavers over compacted basecourse and sand. Available in bags of 10.



NJMS+

Nurajack Mini Spacer + Spike (NJMS+)

The Nurajack Mini Spacer + Spike is designed for installing 20mm tiles/structural pavers over grass. Available in bags of 10.



ADJUSTMENT KEY

Adjustment Key

Nurajacks can be adjusted by the Nurajack Adjustment Key even without the tiles being uplifted.

The Nurajack Adjustment Key simply slips between the tiles and into a slot in the top of the Nurajack or Nurajack Star.T and when turned the Nurajack will adjust up and down. The Nurajack Adjustment Key speeds up installation and is ideal for minor adjustments. If installing heavy or stone concrete paver's, one or two pavers may to be need lifted before adjusting the Nurajack.



SILENT ACOUSTIC PAD

Nurajack SE Acoustic Pads

Footfall noise on any deck area can be minimized through using the Nurajack SE Acoustic Pad.

The Nurajack SE Acoustic Pad is a self-adhesive disc that adheres to the base of the Nurajack.

It will provide a Nurajack SE3 with a total of 25dB (IIC:25) reduction in acoustic transference noise.



NURAJACK SE WINDPROOF

Nurajack SE Windproof

In some extreme situations, tiles may need to be affixed to the Nurajack. The Nurajack SE Windproof is a pedestal especially designed for areas in direct exposure to high winds. When parapets and balustrades do not provide enough protection, the Nurajack SE Windproof pedestal provides the solution.



NURAJACK VERTICAL CLIP

Nurajack Vertical Clip

The Nurajack Vertical Clip will hold 20mm tiles in place vertically under a leading edge of a Nurajack. This is sometimes required when the edge of a deck is exposed or the underside of the deck can be seen through a glass balustrade.



NURAJACK HEAD LOCKER

Nurajack Head Locker

When installing smaller cut tiles adjacent to full tiles, it may be necessary to lock the self-leveling head to stop excessive movement. The Nurajack Head Locker is designed to clip into place and lock the Nurajack's self-leveling head.

Unique Features & Benefits

- **Large Base** - Nurajack's large 330m² base spreads the deck load over the wide base and withstands loads up to 1000kg each. This ensures stability of the deck and maintains the integrity of the waterproof membrane
- **Height-Adjustment Feature** – The height of the Nurajacks can be adjusted from above through use of our Adjustment Key. There is no lifting of tiles to adjust the jacks. This means that the installer can complete the installation with perfect accuracy without the need to remove the tiles
- **Self-Levelling Heads** - The patented self-levelling heads make it easy to create a level deck and a flush indoor-outdoor aesthetic. With Nurajacks there is no longer a need to place ad-hoc shims under the base of the jacks – a time-consuming practice that has the potential to damage the waterproofing membrane through point-loading
- **Ease of Access to Underlying Membrane** - Tiles are removable so membranes and gutters are easily accessible
- **Acoustics** - Nurajack SE Acoustic Pads are available to minimize the noise transference to lower levels
- **Building Code** - Meets Building Code requirements for floated decks over membranes
- **Council Standards** - Meets Council requirements for removable decking over membrane decks
- **Quality Design** – European-designed and manufactured to the highest standards in quality
- **20-Year GUARANTEE**

