



PERFORMANCE GEAR OIL

HIGH PERFORMANCE GEAR OIL

DESCRIPTION:

Performance Gear Oil is a mineral-based gear oil offering unsurpassed performance and protection. Regenerative polymers resist shearing, mechanical breakdown, and viscosity loss of the oil. High viscosity index (VI) formula offers consistent film thickness and performance over a greater operating temperature range. Technologically advanced formula increases horsepower and delivers superior anti-wear and extreme pressure protection from peak loads and elevated temperatures. Surface active chemistry delivers ultra-high film adhesion on gear faces, enabling higher load carrying capability and protecting critical gear interface areas and contact points. Fully formulated additive system contains anti-foam, rust, corrosion, and oxidation protection for high-stress conditions. Exceeds the requirements of API GL-5.

FEATURES & BENEFITS:

- Resists shearing & mechanical breakdown
- Consistent film thickness over various operating temperatures
- Superior protection during peak loads
- Surface-active chemistry aggressively attaches to surfaces, keeping them clean and corrosion-free
- Exceeds API GL-5 specifications

APPLICATIONS:

Performance Gear Oil is recommended for use in rear differentials of high-horsepower racing applications.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	250WT
APPEARANCE	VISUAL	Amber
VISCOSITY @ 40°C (cSt)	D445	481
VISCOSITY @ 100°C (cSt)	D445	47.0
VISCOSITY INDEX	D2270	155
FLASH POINT (°C)	D92	210
POUR POINT (°C)	D97	-18
DENSITY @ 15 °C (g/ml)	D4052	0.878

EXPERIENCE THE DIFFERENCE

Made In The USA