

Released: 2015-07-10

Version: 2.0 Revision Date: 2020-01-28

## 1. IDENTIFICATION OF THE SUBSTANCE / APPLICATION AND THE COMPANY

Supplier:	Product Name: Premium 4T 5W-30, 10W-30, 10W-40, 20W-50, 25W-60
Maxima Racing Oils	Article Number: 39901, 399128, 30-39960, 39505, 39055, 30-20901, 30-209128, 30-20960, 30-20505, 30-20055, 34901, 349128, 30-34960, 34505, 34055, 35901, 359128, 30-35960 35505, 35055, 30-89901, 30-89902
9266 Abraham Way	
Santee, CA 92071 USA	Applications: 4T Engine Oil
+1 619 449 5000	Emergency Telephone: In USA: CHEMTREC +1 703 527 3887 (24 hours)
	Outside USA: +1 619 449 5000

### 2. HAZARDS IDENTIFICATION

GHS Classification	Not classified as hazardous in accordance with OSHA Hazcom 2012
GHS Pictogram	None
Signal Word	None
Hazard Statements	None
Precautionary	
Statements	
Prevention	None
Response	None
Storage	None
Disposal	None
Other Hazards	None

# **3. COMPOSITION / INFORMATION ON INGREDIENTS**

Components	Content %	CAS Number
Petroleum Distillates	70-90	64742-54-7
Proprietary Additives	10-20	Mixture
Zinc alkyldithiophosphate	1-<3	Proprietary

The specific identity and/or exact percentage has been withheld as a trade secret.



Released: 2015-07-10

4. FIRST-AID MEASURES

Version: 2.0 Revision Date: 2020-01-28

Inhalation	If inhaled remove to fresh air. If irritation or difficulty in breathing occurs, get
IIIIdidtioii	medical attention.
Skin Contact	Wash skin with soap and water. Remove clothing and shoes if contaminated. Launder clothing before reuse.
Eye Contact	Flush eyes with water for several minutes, holding the eyelids open. Remove contact lenses, if present and easy to do so. If eye irritation persists, get medical attention.
Ingestion	If conscious, rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.
Most Important	Causes eye irritation. Prolonged skin contact may cause irritation. Inhalation
Symptoms	of vapors or mists may cause respiratory irritation. Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea
Indication of	Immediate medical attention is not required.
Immediate Medical Attention Needed	
Notes to Physician	Treat appropriately

### 5. FIRE FIGHTING MEASURES

Suitable Extinguishing	Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish
Media	flames.
Specific Hazards	This material will burn although it is not easily ignited. Combustion will
Arising From The	produce carbon oxide, zinc oxide and unidentified organic compounds.
Chemical Special Protective Equipment And Precautions For Fire- Fighters	Firefighters should wear full emergency equipment and a NIOSH approved positive pressure self-contained breathing apparatus. Cool exposed intact containers with water

## 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Wear appropriate protective equipment. Wash thoroughly after handling. See also: "Personal Protection "section 8.
Environmental Hazards	Avoid release into the environment. Report spill as required by local and federal regulations.
Methods/Materials for Cleaning up	Dike spill and collect with an inert absorbent. Place into closable containers for disposal. Collected material is handled in accordance with section 13 "Disposal Considerations".



Released: 2015-07-10

# **PREMIUM 4T**

Version: 2.0 Revision Date: 2020-01-28

7. HANDLING AND STORAGE						
Precautions for Safe Handling: Conditions for Safe Storage	Avoid contact with eyes and prolonged or repeated contact with skin and clothing. Avoid breathing vapors and mists. Wash thoroughly after handling. Remove oil-soaked clothing and launder before re-use. Store in a cool area away from oxidizing agents. Protect containers from physical damage.					
8. EXPOSURE CONTROL	S/PERSONAL PROTECTION					
Exposure Limits	Petroleum Distillates 5 mg/m <sup>3</sup> TWA OSHA PEL (as oil Mist) 5 mg/m <sup>3</sup> TWA ACGIH TLV (inhalable) (as mineral oil)					
	Proprietary Additives	None Established				
	Zinc alkyldithiophosphate					
Appropriate Engineering Controls Personal Protection	Good general room ventilation (equivalent to outdoors) should be adequate under normal conditions. If the recommended exposure limit is exceeded increased mechanical ventilation such as local exhaust may be required.					
Respiratory Protection:	None needed under normal use conditions with adequate ventilation. If exposure limits are exceeded, use a NIOSH approved respirator with organic vapor cartridges and particulate pre-filter. Selection of respiratory protection depends on the contaminant type, form and concentration. Select in accordance with OSHA 1910.134 and good Industrial Hygiene practice.					
Eye Protection: Skin/Body Protection: Hand Protection:	Safety glasses or goggles recommended if splashing is possible. No special protective clothing is normally required. If there is a potential for prolonged skin contact, wear a long sleeved shirt and apron. Neoprene or nitrile rubber boots when necessary to avoid contaminating shoes. Use nitrile or neoprene gloves for prolonged or repeated skin contact.					

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Color	Amber
Odor	Slight petroleum odor
Odor Threshold	No data available
рН	No data available
Freezing Point	No data available
Boiling Point	No data available
Flash Point	≥ 220°C
Evaporation Rate	No data available



Released: 2015-07-10

SAFETY DATA SHEET Page 4 of 6

# **PREMIUM 4T**

Version: 2.0 Revision Date: 2020-01-28

Flammability (solid, gas)	No data available
Upper Explosion Limit	No data available
Lower Explosion Limit	No data available
Vapor Pressure	<0.01 mmHg @ 100°F
Vapor Density (Air=1)	>1
Relative Density	0.86-0.88 @ 15.0°C
Solubility	Soluble in hydrocarbons; insoluble in water
Partition Coefficient: n-	No data available
octanol/water	
Auto Ignition	No data available
Temperature	
Decomposition	No data available
Temperature	
Volatile Organic	No data available
Compounds (VOC)	
Viscosity	>20.5 cSt @40°C

#### **10. STABILITY AND REACTIVITY**

Reactivity Chemical Stability Possibility of Hazardous	Not expected to be reactive. Stable. None known.
Reactions	
<b>Conditions to Avoid</b>	None known.
Incompatible Materials	Avoid contact with strong oxidizing agents.
Hazardous Decomposition	ProductThermal decomposition may produce carbon oxides, zinc oxides and unidentified organic compounds.

#### **11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Hazards**

**Eye Contact:** Causes irritation with redness, tearing and pain.

**Skin Contact:** Prolonged or repeated contact may cause mild irritation or dryness. Repeated skin contact may cause dermatitis.

**Inhalation:** Excessive inhalation of vapors or mists may cause upper respiratory tract irritation and central nervous system effects including headache, dizziness and nausea. Breathing high concentrations of oil mists may cause lung damage.

**Ingestion:** Swallowing large amounts may cause gastrointestinal effects including nausea and diarrhea.

**Chronic Effects of Overexposure:** Used motor oils have been found to cause skin cancer in skin painting studies with laboratory animals.

Sensitization: None of the components have been found to cause sensitization in animals or humans.



Released: 2015-07-10

Version: 2.0 Revision Date: 2020-01-28

Mutagenicity: This product is not expected to cause mutagenic activity.

**Reproductive Toxicity:** This product is not expected to cause reproductive or developmental effects. **Carcinogenicity**: None of the components of this product are listed as a carcinogen or suspected carcinogen by IARC, NTP, or OSHA.

#### Acute Toxicity:

Petroleum Distillates Proprietary Additives Zinc alkyldithiophosphate Oral rat LD50 >5000 mg/kg, Dermal rabbit LD50 >2000 mg/kg Oral rat LD50 >2000 mg/kg, Dermal rabbit LD50 >10,000 mg/kg Oral rat LD50 3100 mg/kg, Inhalation rat LC50 >2.3 mg/L/4 hr, Dermal rabbit LD50 >2002 mg/kg

### **12. ECOLOGICAL INFORMATION**

Ecotoxicity		
Petroleum Distillates	96 hr LL50 fish >100 mg/L, 48 hr EL50 daphnia magna >100 mg/L,	
	72 hr EL50 green algae >100 mg/L	
Proprietary Additives	96 LL50 fish 10-100 mg/L, 48 hr EL50 daphnia magna 10-100 mg/L	
Zinc alkyldithiophosphate	e 96 hr LL50 Oncorhynchus mykiss 4.5 mg/kg, 48 hr EL50 daphnia	
	magna 23 mg/L, 72 hr EL50 21 mg/L	
Biodegradation	Petroleum distillates is inherently biodegradable.	
Bioaccumulation	Bioaccumulation Petroleum distillates has the potential to bioaccumulate.	
Mobility in soil	No data available	
Other adverse effects:	None known.	

### **13. DISPOSAL CONSIDERATIONS**

Disposal

Dispose in accordance with all local, state and federal regulations.

### **14. TRANSPORT INFORMATION**

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT		Not Regulated			
TDG		Not Regulated			
IMDG		Not Regulated			
ΙΑΤΑ		Not Regulated			

**Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable – product is transported only in packaged form

Special precautions: None known.



Released: 2015-07-10

Version: 2.0 Revision Date: 2020-01-28

#### **15. REGULATORY INFORMATION**

**CERCLA:** This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**EPA SARA 302:** This product does not contain chemicals regulated under SARA Section 302. **EPA SARA 311 Hazard Classification:** Not hazardous

**EPA SARA 313:** This product contains the following chemicals that are regulated under SARA Title III, section 313:

Zinc alkyldithiophosphate Proprietary 1-<3%

**California Proposition 65:** This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **Chemical Inventories**

Toxic Substances Control Act: All of the components of this product are listed on the TSCA inventory

16. OTHER INFORMATION	

NFPA Rating (NFPA 704):	Health: 2	Fire: 1	Instability: 0
HMIS Rating:	Health: 2	Fire: 1	Physical Hazard: 0

Date of Revision: January 28, 2020 Date of Previous Revision: March 2018 Revision History: 7/10/15: Converted to GHS format. All section revised 9/27/16: Section 2 GHS Classification; Label Elements; Section 3 Composition; Section 4 Eye Contact, Most Important Symptoms; Section 5 Specific Hazards Arising From The Chemical; Section 11 Eye contact; Section 15 SARA 313 11/6/17: Updated emergency telephone #, added 25W-60 3/13/18: Added P/N's for 60 L kegs 1/28/20: New formulation

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.