



# SNG SYN 15W-40

## SYNTHETIC STATIONARY NATURAL GAS ENGINE OIL

### DESCRIPTION:

Maxima's SNG SYN 15W-40 is a premium, low-ash robust stationary natural gas engine oil. SNG 15W-40 is specifically formulated for use in 4-stroke engines with proven performance in gas fuel, gas compression, well gathering, power generation, co-gen, landfill and bio-gas applications. SNG 15W-40 can be used in all original equipment manufacturer (OEM) types of stationary natural gas-fueled engines.

### FEATURES & BENEFITS:

- SNG synthetic provides extended oil life
- Advanced additives improve overall system cleanliness
- Active anti-wear and extreme pressure protection
- Ultra shear-stable polymers maintain consistent viscosity
- Excellent TBN retention
- Outstanding resistance to sludge formation
- Long-term cost savings

### APPLICATIONS:

Wellhead gathering, gas processing plants and storage facilities, gas pipeline and compressor stations, residential electric power plants, industrial electric power plants, irrigation, landfill gas, bio-gas (digesters), coal bed methane, natural gas vehicles.

### TECHNICAL DATA

SPECIFICATION	ASTM	RESULT
SAE VISCOSITY	J300	15W-40
KV @ 40°C	D2270	94.7
KV @ 100°C	D2270	13.9
VISCOSITY INDEX	D2270	149
SULFATED ASH%	D874	0.50
FLASH POINT (°C)	D92	242
POUR POINT (°C)	D97	-30
TBN	D2896	6

**EXPERIENCE THE DIFFERENCE**

**Made In The USA**