

# V-TWIN FORK OIL

## HIGH PERFORMANCE FORK OIL

### **DESCRIPTION:**

Mineral based fork oil designed specifically for use with H-D® Fork Systems. Shear stable, high viscosity index formulation maintains film strength and reduces wear. Advanced, Lubricinol-fortified additive system minimizes stiction and reduces running friction while minimizing foaming and air entrainment. Ultra clean formulation eliminates corrosion, conditions seals and extends equipment life.

#### **FEATURES & BENEFITS:**

- Developed and tested in H-D® Fork Systems
- Lubricinol-fortified formulation reduces overall friction and decreases stiction
- Shear stable, high viscosity index formula maintains film strength and reduces wear
- Maintains optimal damping performance by minimizing foaming and air entrainment
- Keeps internals clean while eliminating corrosion and conditioning seals

#### **APPLICATIONS:**

For all cartridge and standard-type forks. Specifically developed for H-D® Fork Systems.

Maxima V-Twin Fork Oil	H-D Equivalent		
Maxima 5WT	H-D Type B		
Maxima 10WT	H-D Type E		
Maxima 20WT	Screamin' Eagle Heavy		

TECHNICAL DATA					
SPECIFICATION	TEST METHOD	5WT	10WT	20WT	
APPEARANCE	VISUAL	Amber	Amber	Amber	
VISCOSITY @ 40°C (cSt)	D445	16.2	37.4	71.6	
VISCOSITY @ 100°C (cSt)	D445	4.4	7.7	11.3	
VISCOSITY INDEX	D2270	202	182	151	
FLASH POINT (°C)	D92	168	191	210	
POUR POINT (°C)	D97	-33	-27	-24	
DENSITY @ 15 °C (g/ml)	D4052	0.863	0.869	0.871	