

V-TWIN TRANSMISSION/GEAR OIL

HIGH PERFORMANCE GEAR OIL

DESCRIPTION:

Mineral-based gear oil specifically formulated for use in 4-, 5- and 6-speed high performance gear boxes. Robust, shear-stable formulation is designed for Harley-Davidson® transmissions or V-Twin models without wet-clutches. Proprietary shape combines the finest mineral base stocks with industry leading extreme pressure and anti-wear additives to ensure ultimate hardware protection and smooth shifting. Exceeds the requirements of API GL-5.

FEATURES & BENEFITS:

- Formulated specifically for Harley-Davidson® transmissions or V-Twin models without wet-clutches
- Superior protection from wear, pitting and spalling
- Shear stable formula maintains viscosity and ensures smooth shifting
- Surface-active chemistry keeps surfaces free of corrosion, deposits and wear
- Exceeds API GL-5 specifications

APPLICATIONS:

For all Harley-Davidson® transmissions or V-Twin models without wet-clutches. Recommended for use in 4-, 5- and 6-speed high performance gear boxes.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	80W-90	85W-140
APPEARANCE	VISUAL	Amber	Amber
VISCOSITY @ 40°C (cSt)	D445	171.7	331.1
VISCOSITY @ 100°C (cSt)	D445	16.3	26.6
VISCOSITY INDEX	D2270	99	106
FLASH POINT (°C)	D92	203	240
POUR POINT (°C)	D97	-27	-15
DENSITY @ 15 °C (g/ml)	D4052	0.883	0.902