



# **SNG 15W-40**

Version: 1.0

Released: 2018-04-04 Revision Date: 2018-04-04

## 1. IDENTIFICATION OF THE SUBSTANCE / APPLICATION AND THE COMPANY

Supplier: Product Name: SNG 15W-40

Maxima Racing Oils

9266 Abraham Way

Santas CA 02071

Santee, CA 92071

USA

**Applications:** Engine Oil

+1 619 449 5000 **Emergency Telephone:** CHEMTREC +1 703 527 3887 (24 hours)

Article Number: 39-06055, 39-06330

#### 2. HAZARDS IDENTIFICATION

GHS Classification Not classified as hazardous in accordance with

OSHA Hazcom 2012

GHS Pictogram None
Signal Word None
Hazard Statements None

Precautionary Statements

Prevention None
Response None
Storage None
Disposal None

Other Hazards None

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

ComponentsContent %CAS NumberPetroleum Distillates70-9064742-54-7Petroleum Distillates10-30mixture

The specific identity and/or exact percentage has been withheld as a trade secret.

### 4. FIRST-AID MEASURES

**Inhalation** If inhaled remove to fresh air. If irritation or difficulty in breathing occurs, get

medical attention.

**Skin Contact** Wash skin with soap and water. Remove clothing and shoes if contaminated.

Launder clothing before reuse.

**Eye Contact** Flush eyes with water for several minutes. Remove contact lenses, if present

and easy to do so. If eye irritation persists, get medical attention.



# **SNG 15W-40**

Version: 1.0

Released: 2018-04-04 Revision Date: 2018-04-04

If conscious, rinse mouth with water. Do not induce vomiting. Never give Ingestion

anything by mouth to an unconscious person. Get medical attention.

**Most Important** May cause mild eye irritation. Prolonged skin contact may cause irritation.

**Symptoms** Inhalation of vapors or mists may cause respiratory irritation. Swallowing may

cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Indication of

Immediate medical attention is not required.

**Immediate Medical Attention Needed** 

**Notes to Physician** Treat appropriately

#### 5. FIRE FIGHTING MEASURES

Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish Suitable Extinguishing

Media flames.

**Specific Hazards** This material will burn although it is not easily ignited. Combustion will

**Arising From The** produce carbon oxide and unidentified organic compounds.

Chemical

**Special Protective** Firefighters should wear full emergency equipment and a NIOSH approved **Equipment And** positive pressure self-contained breathing apparatus. Cool exposed intact

**Precautions For Fire-**

containers with water

**Fighters** 

# **6. ACCIDENTAL RELEASE MEASURES**

**Personal Precautions** Wear appropriate protective equipment. Wash thoroughly after handling.

See also: "Personal Protection" section 8.

**Environmental Hazards** Avoid release into the environment. Report spill as required by local and

federal regulations.

Methods/Materials for

Dike spill and collect with an inert absorbent. Place into closable containers Cleaning up for disposal. Collected material is handled in accordance with section 13

"Disposal Considerations".

### 7. HANDLING AND STORAGE

**Precautions for Safe** 

Handling:

Avoid contact with skin, eyes and clothing. Avoid breathing vapors and mists. Wear protective clothing and equipment. Wash thoroughly with

soap and water after handling. Remove oil-soaked clothing and launder

before re-use.

**Conditions for Safe** 

Storage

Store in a cool area away from oxidizing agents. Protect containers from

physical damage.

## SAFETY DATA SHEET





# **SNG 15W-40**

Version: 1.0

Released: 2018-04-04 Revision Date: 2018-04-04

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits Petroleum Distillates 5 mg/m3 TWA OSHA PEL (as oil Mist)

5 mg/m3 TWA ACGIH TLV (inhalable)

(as mineral oil)

Appropriate

**Engineering Controls** 

Good general room ventilation (equivalent to outdoors) should be adequate under normal conditions. If the recommended exposure limit is exceeded increased mechanical ventilation such as local exhaust may be required.

**Personal Protection** 

Respiratory Protection:

None needed under normal use conditions with adequate ventilation. If exposure limits are exceeded, use a NIOSH approved respirator with organic

vapor cartridges and particulate pre-filter. Selection of respiratory protection depends on the contaminant type, form and concentration. Select in accordance with OSHA 1910.134 and good Industrial Hygiene

practice.

Eye Protection:

Safety glasses or goggles recommended if splashing is possible.

**Skin/Body Protection:** 

No special protective clothing is normally required. If there is a potential for prolonged skin contact, wear a long sleeved shirt and apron. Neoprene or nitrile rubber boots when necessary to avoid contaminating shoes.

**Hand Protection:** Use nitrile or neoprene gloves for prolonged or repeated skin contact.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Liquid Color Amber

Petroleum odor Odor **Odor Threshold** No data available рΗ No data available No data available **Freezing Point Boiling Point** No data available **Flash Point** No data available No data available **Evaporation Rate** Flammability (solid, gas) No data available **Upper Explosion Limit** No data available **Lower Explosion Limit** No data available <0.01 mmHg @ 100°F **Vapor Pressure** 

Vapor Density (Air=1) >1

**Relative Density** No data available

**Soluble** in hydrocarbons; insoluble in water

Partition Coefficient: n-

octanol/water

No data available

# SAFETY DATA SHEET





# **SNG 15W-40**

Version: 1.0

Released: 2018-04-04 Revision Date: 2018-04-04

Auto Ignition No data available

**Temperature** 

**Decomposition** No data available

Temperature

Volatile Organic No data available

Compounds (VOC)

Viscosity >20.5 cSt @ 104°F

#### 10. STABILITY AND REACTIVITY

**Reactivity** Not expected to be reactive.

**Chemical Stability** Stable.

**Possibility of Hazardous** None known.

Reactions

**Conditions to Avoid** Avoid temperatures over 120°F, open flames and sparks.

**Incompatible Materials** Avoid contact with strong oxidizing agents.

Hazardous Decomposition Product Thermal decomposition may produce carbon oxides and

unidentified organic compounds.

#### 11. TOXICOLOGICAL INFORMATION

#### **Potential Health Hazards**

**Eye Contact:** May cause mild irritation.

**Skin Contact:** Prolonged or repeated contact may cause mild irritation or dryness. Repeated skin contact may cause dermatitis.

**Inhalation:** Excessive inhalation of vapors or mists may cause upper respiratory tract irritation and central nervous system effects including headache, dizziness and nausea. Breathing high concentrations of oil mists may cause lung damage.

**Ingestion:** Swallowing large amounts may cause gastrointestinal effects including nausea and diarrhea.

**Chronic Effects of Overexposure:** Used motor oils have been found to cause skin cancer in skin painting studies with laboratory animals.

Sensitization: None of the components have been found to cause sensitization in animals or humans.

**Mutagenicity:** This product is not expected to cause mutagenic activity.

**Reproductive Toxicity:** This product is not expected to cause reproductive or developmental effects. **Carcinogenicity:** None of the major components of this product are listed as a carcinogen or

suspected carcinogen by IARC, NTP, or OSHA.

**Acute Toxicity:** 

Petroleum Distillates Petroleum Distillates (CAS 64742-54-7): Oral rat LD50 >5000 mg/kg,

Inhalation rat LC50 >5.5 mg/L/4 hr (mist), Dermal rabbit LD50 >2000

mg/kg

Petroleum Distillates Petroleum Distillates (mixture): ATEmix > 10,000 mg/kg (oral)



# **SNG 15W-40**

Version: 1.0

Released: 2018-04-04 Revision Date: 2018-04-04

### 12. ECOLOGICAL INFORMATION

**Ecotoxicity** 

Petroleum Distillates Petroleum Distillates (CAS 64742-54-7): LL50 fish >100 mg/L, EL50

aquatic invertebrates > 100 mg/L, EL50 algae > 100 mg/L

Petroleum Distillates Petroleum Distillates (mixture): 4 d LC50 Fathead Minnow >100

mg/L, 21 d EC50 Dapnia magna > 10 mg/L, 3 d EC50 Scenedesmus

quadricauda > 100 mg/l

**Biodegradation** Petroleum distillates (CAS 64742-54-7): Not readily biodegradable.

Petroleum distillates (mixture): Not readily degradable (31 %, 28 d, OECD

TG 301B).

**Bioaccumulation** Petroleum distillates (CAS 64742-54-7) have a log Kow of > 5.3 which

suggests a potential for bioaccumulation.

Petroleum distillates (mixture) have the potential to bioaccumulate.

**Mobility in soil** The product is not water soluble (floats on water) and may be adsorbed to

soil particles.

Other adverse effects: None known.

#### 13. DISPOSAL CONSIDERATIONS

**Disposal** Dispose in accordance with all local, state and federal regulations.

## 14. TRANSPORT INFORMATION

	UN	Proper shipping name	Hazard	Packing	Environmental
	Number		Class	Group	Hazard
DOT		Not Regulated			
TDG		Not Regulated			
IMDG		Not Regulated			
IATA		Not Regulated			

**Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable – product is transported only in packaged form

Special precautions: None known.

# SAFETY DATA SHEET





# **SNG 15W-40**

Version: 1.0

Released: 2018-04-04 Revision Date: 2018-04-04

## 15. REGULATORY INFORMATION

**CERCLA:** This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

EPA SARA 302: This product does not contain chemicals regulated under SARA Section 302.

EPA SARA 311 Hazard Classification: Not hazardous

**EPA SARA 313:** This product contains the following chemicals that are regulated under SARA Title III, section 313: None

**California Proposition 65:** This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **Chemical Inventories**

Toxic Substances Control Act: All of the components of this product are listed on the TSCA inventory

### **16. OTHER INFORMATION**

NFPA Rating (NFPA 704): Health: 1 Fire: 1 Instability: 0 HMIS Rating: Health: 1 Fire: 1 Physical Hazard: 0

Date of Revision: April 4, 2018
Date of Previous Revision: N/A

Revision History: New document.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.