Specifications

♦IP110H

General

Operating temperature range: −10°C ~ +60°C, 14°F ~ 140°F

Humidity: Less than 95% (Without condensation)

• Dimensions: 57.0 (W) × 96.9 (H) × 25.1 (D) mm, 2.2 (W) × 3.8 (H) × 1.0 (D) inches

(Projections not included)

Weight: Approximately 146 g, 5.2 oz
Power supply: 3.75 V DC (Internal battery)

• IP code: IP67/IP54

Operating time: Approximately 26.5 hours (TX : RX : Stand-by = 1 : 1 : 8)

Audio

• Codec: G.711 μ-law (64 kbps)

· AF output power:

Internal speaker More than 1000 mW (at 10% distortion into an 8 Ω load) External speaker More than 300 mW (at 10% distortion into an 8 Ω load)

AF output impedance:

 $\begin{array}{ll} \text{Internal speaker} & 8 \ \Omega \\ \text{External speaker} & 8 \ \Omega \end{array}$

WLAN

Wireless LAN standard: IEEE802.11 n/a/b/g/ac

• Authentication and Encryption: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES)

· Channels:

EXP version 13 channels (2.4 GHz band) 19 channels (5 GHz band) USA version 11 channels (2.4 GHz band)

21 channels (5 GHz band)

① May differ depending on the country of use.Protocol: TCP/IP

Output power (typical): Less than 10 mW/MHz

Bluetooth

• Frequency range: 2402 ~ 2480 MHz

• Transmission power: Class 2

• Version: Bluetooth Version 4.2

Profile: HFP, HSP

♦BC-257

Input voltage: 5.0 V ± 0.25 V DC (Used with a 5 V/2 A output AC adapter)

 $15 \text{ V} \pm 0.75 \text{ V}$ DC (Used with the BC-228)

• Charging temperature range: 0°C ~ 40°C, 32°F ~ 104°F

• Dimensions: 98.0 (W) × 48.6 (H) × 70.0 (D) mm, 3.9 (W) × 1.9 (H) × 2.8 (D) inches

(With the charger's covers)

Weight: Approximately 94 g, 3.3 oz

① All stated specifications are subject to change without notice or obligation.