

# MATERIAL SAFETY DATA SHEET

## SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MSDS Name : Fast Drying Adhesive Synonym(s): None  
General : Adhesive  
Company Identification : Lethal Lashes  
: 62 Countryside Place Spruce Grove, Alberta Canada

## SECTION 2 – COMPOSITION, INFORMATION ON INGREDIENTS

COMPONENT	CAS. NO	% BY WEIGHT(APPROX.)
Polyamide Resin	88384-96-7	1%>
Alkoxy2 – Cyanoacrylate	7085-85-0	90%>
Polymethyl Methacrylate	9011-14-7	9 %>
Exposure	*Ingredient which have exposure limits	
Ingredients	ACGIH (TLV) OSHA (PEL) OTHER	

## SECTION 3 – HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

Vapor is irritating to eyes, skin and mucous membranes and respiratory tract.

### POTENTIAL HEALTH EFFECTS

May caused sensitization by inhalation, Narcotic effects, headache, dizziness, vomiting.

Skin : Dryness

Eye : Irritation

### POTENTIAL ENVIROMENTAL EFFECTS:

Not available.

### SIGN AND SYMPTOMS OF EXPOSURE:

Vapor is irritating to eyes and mucous membranes above TLV.

Prolonged and repeated over exposure to vapors may cause symptoms of non-allergic asthma in sensitive individuals.

### EXISTING CONDITIONS AGGRAVATED BY EXPOSURE:

None Known

## SECTION 4 – FIRST AID MEASURES

Ingestion : Ingestion is not likely. See supplemental page for emergency procedures.  
Inhalation : Evacuate from further exposure. If unconsciousness occurs, see immediate medical assistance and call a physician. If the breath has stopped, have artificial respiration. If breathing difficulty occurs, have oxygen inhalation.  
Skin contact : Remove contaminated clothing. Wash contact areas with soap and water.  
Eye contact : Flush with water thoroughly for at least 15 minutes. Seek immediate medical assistance.

---

## SECTION 5 – FIRE FIGHTING MEASURE

---

Flash Point : above 115°C Method: Cleveland open cup. (Recommended)  
Extinguishing Agents : Carbon dioxide, foam, dry chemical  
Special Firefighting Procedures: Not Available  
Hazardous Products Formed by fire or thermal decomposition: Irritating organic fragments  
Unusual fire or explosion hazards: None  
Explosive Limits: (% by volume in air) Lower Not available  
: (% by volume in air) Upper Not available

---

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

---

Evacuate non-essential personnel.  
Shut off all sources of ignition: No fires, smoking or flames in area.  
\* Ventilate area after material pick up is completed.

For small spill:

Absorb spill with inert material (dry cloth, dry sand), then place in a chemical waste containers using non-sparking tools.

Flush residual spill (area) with plenty of water.

For large spill:

Dike for later disposal.

Wash with plenty of water.

---

## SECTION 7 – HANDLING AND STORAGE

---

HANDLING:

Keep away from sources of ignition and heat. No smoking or flames in working area.

Take precautionary measures against static discharges.

Wear proper protective equipment, and avoid contact with skin or eyes.

Use only in well ventilated areas.

Use exhaust ventilation to keep air concentration below exposure limit.

Keep container tightly closed when not in use.

Install emergency showers and eye wash facility in working area.

STORAGE:

Keep away from possible source of ignition.

Store in cool, dry and well ventilated location.

Keep container tightly closed.

Keep away from combustible materials, hear, and steam pipe or sunlight.

Keep away from oxidizing materials.

OTHER PRECAUTIONS:

Wash hands, face and gargle after work.

Practice good personal hygiene after using this material, especially before eating, drinking, smoking or using the rest room.

Keep out of reach of children.

---

## SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

---

Respiratory protection (Specify type): Chemical Cartridge respirator with organic vapor

Ventilation Local exhausts

---

Should be used control vapors in work area.

Mechanical (general)

Should use a breathing mask

Protective gloves: Polyethylene gloves.

No rubber Eye protection Safety glasses, face shield.

Skin Protection: Other protective clothing or equipment impervious Clothing apron and boots barrier dream ETC.

---

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

---

Appearance	: Black Liquid
Odor	: Sharp, irritating
Boiling Point	: Above 190°c (374. F)
Melting Point	: N/A
Specific Gravity (H2O = 1)	: 0.9-1.1
Vapor Pressure (at 25°c)	: 1Pa
Vapor Density (Air =1)	: 4.5
Evaporation Rate (Butyl acetate =1)	: N/A
Solubility in Water: Insoluble (Polymerized by water)	

---

## SECTION 10 – STABILITY AND REACTIVITY

---

Condition to avoid	: High humidity, high temperature or direct sunlight
Stability	: Stable (Cool and dry area)
Material to avoid	: Polymerized by contact with water, alcohols, amines or alkalis.
Hazardous Decomposition or by Products:	CO2, Oxides, Nitrogen and unknown Hydrocarbons.

---

## SECTION 11 – TOXICOLOGICAL INFORMATION

---

Toxicity : Skin contact may cause burns, bond skin rapidly and strongly skin and eye irritant

Skin and eye may be irritant.

Routes of entry : Inhalation (Yes), Skin(Yes), Ingestion (Yes)

Carcinogen etc: See section 3

---

## SECTION 12 – ECOLOGICAL INFORMATION

---

No date Available.

---

## SECTION 13 – DISPOSAL CONSIDERATIONS

---

Waste disposal method: Don't pour drain. Follow domestic and local environmental regulations.

Precautions to be taken in handling and storing: Avoid unnecessary exposure to air and moisture.

Don't store above 25°c and in direct sunlight.

Keep container lids tightly closed.

Other Precautions: Wear recommended equipment to avoid contact with skin and eyes. Protect eyes, skin and clothing from contact with liquid product.

---

## SECTION 14 – TRANSPORTATION INFORMATION

---

U.S Department of Transportation Ground Transport (49 CFR 172)  
Proper Shipping Name : Unrestricted (Not more than 450 liters.)  
Combustible liquids n.o.s. (Cyanoacrylate ester) (More than 450 liters)  
Hazard class or division : Unrestricted (Not more than 4 50 liters.)  
Combustible liquids (More than 450 liters)  
Identification number : None (Not more than 450 liters.)  
NA1993 (More than 450 liters)  
Marine Pollutant : None  
International Air Transportation (ICA/IATA)  
Proper shipping name : Unrestricted  
Class or Division : Unrestricted  
UN or ID number : None  
Water Transportation (IMO/IMDG)  
Proper Shipping Name : Unrestricted  
Hazard class or division: None  
Identification Number : None  
Marine Pollutant : None

---

## SECTION 15 – REGULATORY INFORMATION

---

CA Proportion 65: No California Proposition 65 chemicals are known to be present.  
TSCA 8(b) Inventory Status: All components are listed or are exempt from listing on Toxic Substances Control Act Inventory  
EINECS All components are listed on EINECS

---

## SECTION 16 – OTHER INFORMATION

---

Estimated NFPA(R) Code:  
Health Hazard : 1  
Fire Hazard : 1  
Reactivity Hazard : 1  
Specific Hazard : Does not apply

Estimated HMIS(R) Code:  
Health Hazard : 1  
Flammability Hazard : 1

NFPA is a registered trademark of the National Fire Protection Assn.  
HMIS is a registered trademark of the National Paint and Coating Assn.