520mm ONBOARD UNDERMOUNT RANGEHOOD - SINGLE MOTOR

SL906DL520





Rangehood type	Undermount
Control	Button
Speed settings	4
Ducting diameter	150mm
Extraction type	Onboard motor
Green Energy Motor	Single aluminium motor
Extraction	1020m³/h
Filter	25mm stainless steel baffle
Dynamic Lighting	Adjustable and dimmable lighting
Induction Countdown Control	Yes
Electrical requirement	10A
Dimensions (mm)	W520 x D290 x H350
Weight	17kg
Cut-out dimensions (mm)	W501 x D265
Warranty	3 years (6 years when Sirius ducting is used)



SINGLE MOTOR



FILTERS




1020m³/h AIRFLOW








Ducting options



*Product dimension includes trim





Roof ducted

Eave or Wall ducted

- Use semi-rigid or rigid ducting, not fully flexible foil ducting.
- Fewer bends means a quieter and more powerful extraction.
- Bonus 3 years warranty when Sirius ducting is used (total 6 years).
- See <u>support page</u> on Sirius website for installation videos and FAQs.

WARNING: technical specifications and product sizes can be varied by the manufacturer, without notice. Cut outs for appliances should only be by physical product measurements. The above information is indicative only.

Distributed by Arisit Pty Ltd