




POWDER COATED TOUGH



YouTube




STANDARD LOOP STYLE



HOT DIPPED GALVANIZED FINISH SHOWN. OTHER SPECIALTY FINISHES AVAILABLE, CONTACT FACTORY.



PIN STYLE • Suffix P



REAR SPACER • Suffix RS

Rear Spacer (suffix RS): Load pallets into rear of trailer conveniently and easily. Practical for pushing pallets two or three deep into a trailer. This option is factory installed and must be ordered with fork extensions. Contact factory for pricing.

Fork Extensions

Provide the extra support needed to lift long or large objects with a fork truck. Welded steel construction with cast steel tips. Steel retaining strap (loop style) prevents fork extensions from sliding off forks during use. Baked-in powder-coated toughness. OSHA regulations require that extensions are no more than 150% of the existing fork length. (e.g. 48" existing forks, the fork extension should not exceed 72"). Maximum uniform capacity is 4,000 pounds evenly distributed per pair.

Loop Style: Insert loop at the tip of the fork and slide it up at a 45° angle. Then, lay it down over the existing fork.

Pin Style (suffix P): Remove pin and lay extension over fork or drive fork truck into the extension. Re-insert the pin behind the heel of the fork to secure extension.

MODEL NUMBER	ACCOMMODATES FORK WIDTH	FORK EXTENSION INSIDE WIDTH	USABLE LENGTH	MAXIMUM FORK THICKNESS	WEIGHT PAIR (LB.)
LOOP STYLE					
FE-4-48	4"	4½"	48"	2"	74
FE-4-54	4"	4½"	54"	2"	84
FE-4-63	4"	4½"	63"	2"	98
FE-4-66	4"	4½"	66"	2"	100
FE-4-72	4"	4½"	72"	2"	114
FE-4-84	4"	4½"	84"	2"	145
FE-4-90	4"	4½"	90"	2"	166
FE-4-96	4"	4½"	96"	2"	172
FE-5-48	5"	5½"	48"	2"	86
FE-5-54	5"	5½"	54"	2"	96
FE-5-63	5"	5½"	63"	2"	110
FE-5-66	5"	5½"	66"	2"	116
FE-5-72	5"	5½"	72"	2"	128
FE-5-84	5"	5½"	84"	2"	160
FE-5-90	5"	5½"	90"	2"	179
FE-5-96	5"	5½"	96"	2"	191
FE-6-48	6"	6½"	48"	2½"	94
FE-6-54	6"	6½"	54"	2½"	104
FE-6-63	6"	6½"	63"	2½"	116
FE-6-66	6"	6½"	66"	2½"	128
FE-6-72	6"	6½"	72"	2½"	134
FE-6-84	6"	6½"	84"	2½"	190
FE-6-90	6"	6½"	90"	2½"	204
FE-6-96	6"	6½"	96"	2½"	218
PIN STYLE					
FE-4-48-P	4"	4½"	48"	2"	75
FE-4-54-P	4"	4½"	54"	2"	85
FE-4-63-P	4"	4½"	63"	2"	99
FE-4-66-P	4"	4½"	66"	2"	101
FE-4-72-P	4"	4½"	72"	2"	115
FE-4-84-P	4"	4½"	84"	2"	155
FE-4-90-P	4"	4½"	90"	2"	167
FE-4-96-P	4"	4½"	96"	2"	173
FE-4-108-P	4"	4½"	108"	2"	193
FE-4-120-P	4"	4½"	120"	2"	220
FE-5-48-P	5"	5½"	48"	2"	87
FE-5-54-P	5"	5½"	54"	2"	97
FE-5-63-P	5"	5½"	63"	2"	111
FE-5-66-P	5"	5½"	66"	2"	117
FE-5-72-P	5"	5½"	72"	2"	129
FE-5-84-P	5"	5½"	84"	2"	161
FE-5-90-P	5"	5½"	90"	2"	180
FE-5-96-P	5"	5½"	96"	2"	192
FE-5-108-P	5"	5½"	108"	2"	216
FE-5-120-P	5"	5½"	120"	2"	230
FE-6-48-P	6"	6½"	48"	2½"	95
FE-6-54-P	6"	6½"	54"	2½"	105
FE-6-63-P	6"	6½"	63"	2½"	117
FE-6-66-P	6"	6½"	66"	2½"	129
FE-6-72-P	6"	6½"	72"	2½"	135
FE-6-84-P	6"	6½"	84"	2½"	187
FE-6-90-P	6"	6½"	90"	2½"	190
FE-6-96-P	6"	6½"	96"	2½"	214
FE-6-108-P	6"	6½"	108"	2½"	216
FE-6-120-P	6"	6½"	120"	2½"	230