



48 Hours
to Ship

TYPE A



TYPE B


POWDER
COATED
TOUGH

ours
to Ship



P-38-50

ours
to Ship



16L

POWDER
COATED
TOUGH



model
ECR-45-S



model
ECR-45-D



model
ECR-50

Deluxe Spring Driven Low Pressure Hose Reels

Keep air hoses off the floor and out of the way. Minimize labor, save storage space, protect against trip hazards and damaged hoses. For use with air and water only. Solid steel construction with heavy-duty brackets to resist hose pull. All reels have a full shaft and swivel to assure maximum product delivery. Maximum temperature is 150° F. Maximum pressure is 300 psi / 21 bar. Includes self retracting hose.

| TYPE | MODEL NUMBER | OVERALL SIZE (W x D x H) | INSIDE HOSE DIAMETER | LENGTH OF HOSE | WEIGHT (POUND) |
|------|--------------|--------------------------|----------------------|----------------|----------------|
| A | VHR-20-44 | 6¼" x 15" x 15" | 1/4" | 20 FOOT | 19 |
| A | VHR-35-44 | 5½" x 12½" x 13" | 1/4" | 35 FOOT | 31 |
| A | VHR-17-46 | 6" x 15" x 15½" | 3/8" | 17 FOOT | 31 |
| A | VHR-25-46 | 6½" x 14¾" x 15½" | 3/8" | 25 FOOT | 26 |
| A | VHR-50-56 | 7½" x 19½" x 20" | 3/8" | 50 FOOT | 43 |
| B | VHR-35-58 | 8" x 9¼" x 18" | 1/2" | 35 FOOT | 43 |
| B | VHR-50-78 | 8¼" x 21" x 19¾" | 1/2" | 50 FOOT | 55 |

Standard Spring Driven Low Pressure Hose Reels

Keep air hoses off the floor and out of the way. Minimize labor, save storage space, protect against trip hazards and damaged hoses. Maximum pressure is 300 psi / 20 bar. Includes self retracting hose.

Model SHR-P-38-50 is constructed of durable, high quality impact resistant polypropylene. A positive latching mechanism automatically locks hose at a desired length. A safety lock prevents the hose from moving in either direction. An integral wall/overhead swivel bracket and 36" lead hose are included. Maximum temperature is 140° F.

| MODEL NUMBER | DESCRIPTION | OVERALL SIZE (W x D x H) | INSIDE HOSE DIAMETER | LENGTH OF HOSE | WEIGHT (POUND) |
|--------------|-------------|--------------------------|----------------------|----------------|----------------|
| SHR-P-38-50 | PLASTIC | 8¾" x 17½" x 17¼" | 3/8" | 50 FOOT | 23 |

Air Hose Reel

Help eliminate twists and tangles of hoses, save storage space, protect against trip hazards and damaged hoses with Air Hose Reels. This arm style reel is constructed of all steel. Quick and simple manual hand crank and spring loaded axle helps reel in up to 100 feet of 3/8" hose or 50 feet of 1/2" hose. Valve assembly is rated at 100 psi and 25 cfm. Unit can be mounted both vertically or horizontally. The wall bracket measures 7"W x 3"H. Hose is not included.

| MODEL NUMBER | DESCRIPTION | OVERALL SIZE (W x D x H) | USABLE SPACE | WEIGHT (POUND) |
|--------------|-------------|--------------------------|--------------|----------------|
| REEL-16L | ARM STYLE | 14" x 17¾" x 18" | 5" | 14 |

Electric Cord Reels 115V 1-PHASE STANDARD

Help eliminate the danger of tangled electrical cords with these Electric Cord Reels. The compact design is spring retractable and engineered for industrial use. Complete with 4 foot pigtail and three prong plug, 115V, 60 Hz single phase. Ideal for indoor non-weather tight applications only. UL listed and CSA certified.

Model ECR-45-S comes with a 15 AMP 3 wire single receptacle with clamp type strain relief.

Model ECR-45-D features a duplex outlet box and ground fault circuit interrupter.

Comes with a 20 AMP 3 wire double receptacle.

Model ECR-50 has an incandescent lamp and single receptacle. Head has tool tap, push through winch and metal grounded guard. 75 watt bulb maximum. Bulb not included.

| MODEL NUMBER | DESCRIPTION | CORD LENGTH | WIRE GAUGE | WEIGHT (POUND) |
|--------------|----------------------|-------------|------------|----------------|
| ECR-45-S | SINGLE RECEPTACLE | 45 FEET | 12 | 24 |
| ECR-45-D | DOUBLE RECEPTACLE | 45 FEET | 12 | 31 |
| ECR-50 | LAMP WITH RECEPTACLE | 50 FEET | 16 | 25 |