



series CYL-LT



model CYL-HLT

Portable Cylinder Lifters

Easily move and lift cylinders for placement into portable welders. Lift cylinders up to 14" high. For use with maximum cylinder height of 56" and a maximum cylinder diameter of 11½". Cylinder is secured to cart with manual ratchet strap. Cylinder is raised and lowered with manual hand crank cable winch. Portable with two (2) 10" wheels. Steel construction with yellow baked-in powder-coated toughness. Uniform capacity is 300 pounds.

MODEL NUMBER	OVERALL SIZE (W x D x H)	WHEEL TYPE	WHEEL SIZE	WEIGHT (POUND)
CYL-LT-1-HR	17 ⁵ / ₈ " x 23 ³ / ₈ " x 79 ⁵ / ₁₆ "	HARD RUBBER	(2) 10" x 2½"	106
CYL-LT-1-PN	17 ⁵ / ₈ " x 23 ³ / ₈ " x 79 ⁵ / ₁₆ "	PNEUMATIC	(2) 10" x 3½"	102

Cylinder Lifter/Transporter

Perfect for transporting gas cylinders and loading them onto a truck. This unit raises cylinders by simply turning a mechanical hand crank to the desired height. Cylinder is held in place with a tough polyester webbing strap that guards against damage and slipping. Maximum cylinder diameter 11½" by 56" tall.


MODEL NUMBER	OVERALL SIZE (W x L x H)	HEIGHT TO BOTTOM OF CYLINDER	UNIFORM CAPACITY	WEIGHT (POUND)
CYL-HLT	37 ¹ / ₃₂ " x 48 ¹⁵ / ₁₆ " x 85 ²⁹ / ₃₂ "	40"	300 lb.	305



model CYL-E

model CYL-EH-FP

model CYL-2



TORCH BOX



Welding Cylinder Torch Carts

Designed for transporting cylinders and cutting torch. Includes two (2) tank compartments with heavy-duty ratchet straps. Brackets are included for holding cutting torch and hose. Sturdy handles and large 16" diameter wheels for tilt-n-go portability. Heavy-duty uniform capacity rating is 500 pounds. Convenient open-top storage tray included on all CYL-E series carts only. CYL-2 models include lockable storage box for regulators. Box includes hose opening so regulator does not need to be disconnected for storage. Lifting eye is 2" maximum diameter, material thickness is 7/16". Fork pockets for transportation is included on CYL-2 models. Usable size of each fork pocket is 7½"W x 2³/₁₆"H. Units with fire protection include ½" (approximately 13mm) marineite 1 material, which provides a 30 minute fire protection barrier as described by OSHA standards 1910.253 and 1926.350. Welded steel construction with a yellow, baked-in powder-coated toughness. Not designed for use as a storage means for gas cylinders.



Raise with hoist, lift with fork truck, or manually push around.

Models CYL-2-G & CYL-2-FF-G feature a hot dipped galvanized finish.



model CYL-2-FF



model CYL-2-G

CA Residents see WARNING A, Pg. 459

MODEL NUMBER	WHEEL TYPE	CUTTING TORCH BOX	OVERHEAD LIFT EYE	FORK POCKETS	OVERALL SIZE (W x L x H)	FIRE PROTECTION	WEIGHT (POUND)
CYL-E	PNEUMATIC	NO	NO	NO	34½" x 23" x 57"	NO	144
CYL-E-FF	FOAM-FILLED	NO	NO	NO	34½" x 22 ¹³ / ₁₆ " x 57"	NO	150
CYL-EH	PNEUMATIC	NO	YES	NO	34½" x 23" x 66 ³ / ₈ "	NO	172
CYL-EH-FF	FOAM-FILLED	NO	YES	NO	34½" x 22 ¹³ / ₁₆ " x 66 ³ / ₈ "	NO	185
CYL-EH-FP	PNEUMATIC	NO	YES	NO	34½" x 23" x 66 ³ / ₈ "	YES	194
CYL-EH-FP-FF	FOAM-FILLED	NO	YES	NO	34½" x 22 ¹³ / ₁₆ " x 66 ³ / ₈ "	YES	224
CYL-2	PNEUMATIC	YES	YES	YES	40¼" x 34 ⁹ / ₁₆ " x 66 ³ / ₈ "	NO	278
CYL-2-FF	FOAM-FILLED	YES	YES	YES	40¼" x 34 ⁹ / ₁₆ " x 66 ³ / ₈ "	NO	306
CYL-2-FP	PNEUMATIC	YES	YES	YES	40¼" x 34 ⁹ / ₁₆ " x 66 ³ / ₈ "	YES	305
CYL-2-FP-FF	FOAM-FILLED	YES	YES	YES	40¼" x 34 ⁹ / ₁₆ " x 66 ³ / ₈ "	YES	336
CYL-2-G	PNEUMATIC	YES	YES	YES	40¼" x 34 ⁹ / ₁₆ " x 66 ³ / ₈ "	NO	275
CYL-2-FF-G	FOAM-FILLED	YES	YES	YES	40¼" x 34 ⁹ / ₁₆ " x 66 ³ / ₈ "	NO	302