

Electric Drum Pumps 115V 1-PHASE STANDARD

Reduce time required to dispense or transfer liquids. Electric drum pumps allow you to move fluid easily and efficiently. Pumps come complete with tube for 2" bung, hose, and 115V motor.

FHL-PUMP for Flammables & Hazardous Locations

ME I 6 EX motor, Class I Group C&D, Class II Groups F&G (Explosion Proof) with 16 ft. cord, pump tube SS 39" sealless, high volume rotor, 1" SS barrel adaptor, 1" SS nozzle with swivel, 8' conductive chemical tubing with conductive fittings, ground & bonding wires, wall hanger.

ODF-PUMP for Thin-Bodied Oils & Diesel Fuel

B36 motor with 16 ft. cord, pump tube ALU 39" sealless, high head impeller, 316 stainless steel shaft, PP Barrel Adaptor, 1" aluminum nozzle with swivel, 8" PVC hose, hose clamps, and wall hanger.

ABS-PUMP for Acids & Base Solutions

B36 motor with 16 ft cord, pump tube PP 39" sealless, high volume rotor, Hastelloy C shaft, PP barrel adaptor, 3/4" PP nozzle, 8' PVC hose, hose clamps, and wall hanger.

HCB-PUMP for Highly Corrosive Acids & Base Solutions

B55T-5 motor with 16 ft. cord, pump tube PVDF 39" sealless, high volume rotor, Hastelloy C shaft, PP barrel adaptor, 1" PVDF nozzle with swivel, 8' chemical hose, hose clamps, and wall hanger.



model EDP



model FHL-PUMP



model ODF-PUMP



model ABS-PUMP



model HCB-PUMP

| MODEL NUMBER | MAXIMUM VISCOSITY | MAXIMUM CAPACITY | MAXIMUM HEAD | MAXIMUM S.G. | IMMERSION DEPTH | WEIGHT (POUND) |
|------------------|-------------------|------------------|--------------|--------------|-----------------|----------------|
| EDP [Ⓢ] | 400 CPS | 22.75 GPM | 43 FT. | 1.3 | 39" | 20 |
| FHL-PUMP | 500 CPS | 18.5 GPM | 33 FT. | 1.3 | 12" | 21 |
| ODF-PUMP | 500 CPS | 15.9 GPM | 68 FT. | 1.4 | 12" | 21 |
| ABS-PUMP | 600 CPS | 13.5 GPM | 31 FT. | 1.4 | 12" | 18 |
| HCB-PUMP | 500 CPS | 13.5 GPM | 26 FT. | 1.6 | 39" | 35 |

Fire Extinguisher Carrier

The Fire Extinguisher Carrier is designed for easily transporting your fire extinguisher up to 8" in diameter. Includes two (2) heavy duty adjustable rubber straps. Sturdy handle with rubber grip and poly casters for tilt-n-go portability. Welded steel construction with yellow baked-in powder-coat toughness. 4" x 2" stabilizing plate keeps unit upright when empty and helps retain extinguisher. Adjustable EPDM restraining straps keep extinguisher secure and allow for quick access. Wall mount bracket included to store the extinguisher off the floor.

| MODEL NUMBER | OVERALL SIZE (W x L x H) | WHEEL TYPE | WHEEL SIZE | WEIGHT (POUND) |
|--------------------|--|--------------|--------------------------------------|----------------|
| FEC-1 [Ⓢ] | 14 ³ / ₈ " x 11 ¹ / ₈ " x 41 ³ / ₈ " | POLY-ON-POLY | 4" x 1 ¹ / ₄ " | 13 |



model FEC-1

Wall Mounted Cylinder Brackets

Simple design is easy to install. Simply bolt to wall and then secure cylinder with strap. Edges are protected with rubber guards on the steel units. Choose either steel or molded plastic construction. Maximum 12" cylinder diameter. Installation hardware is not included.



model CB-W-S




model CB-W-2S



model CB-W-P



model CB-W-3S



model CB-W-2P

| MODEL NUMBER | MATERIAL | ACCOMMODATES CYLINDERS | WEIGHT (POUND) |
|----------------------|----------|------------------------|----------------|
| CB-W-S [Ⓢ] | STEEL | 1 | 2 |
| CB-W-2S [Ⓢ] | STEEL | 2 | 7 |
| CB-W-3S [Ⓢ] | STEEL | 3 | 10 |
| CB-W-P [Ⓢ] | PLASTIC | 1 | 1 |
| CB-W-2P [Ⓢ] | PLASTIC | 2 | 2 |