

BEST model FL-ADJ-810



Suction cup bottom pad



These one of a kind floor locks include an adjustable height foot pad that will work on carts with different caster heights. The adjustable height feature provides uniform locking and safety unlocking force for better ergonomic operation. This feature also keeps the floor lock working properly as spring and pads wear over time. Height is adjustable by turning the bottom pad. The bottom pad includes suction-cups for extra grip.

MODEL	EXTENDED	RETRACTED	USED WITH	WEIGHT
NUMBER	HEIGHT	HEIGHT	CASTER SIZE	(POUND)
STEEL CONSTRUCTION				
FL-ADJ-46	6¼" to 8"	5½" to 7¼"	4" - 6"	7
FL-ADJ-810	81/4" to 111/2"	61/4" to 91/2"	6" - 8"	9
STAINLESS STEEL CON	STRUCTION			
FL-ADJ-46-SS	61/4" to 8"	5½" to 7¼"	4" - 6"	7
FL-ADJ-810-SS	8¼" to 11½"	61/4" to 91/2"	6" - 8"	9

Low Profile Floor Lock

The lowest-profile floor lock available on the market today. Features adjustable-height pad for precision and wearability, simply bolt to bottom of cart. Foot operated. Heavy-duty cast steel construction.

MODEL	EXTENDED	RETRACTED	WEIGHT
Number	Height	Height	(POUND)
FL-LK-LP	49/16"	33/4"	6

General Purpose Floor Locks

Floor Locks may be used on platform trucks, fixture dollies, or equipment with casters. Simple foot pressure immobilizes equipment. Locks when large friction face is pressed against the floor. To release simply kick release rod. Brake is independent of casters and can be installed to any convenient location on the cart. Vertical mounting plate designed to mount to sides of carts and other portable products. The spring loaded pad accommodates uneven floors. Units mount with pad 1½" off the floor when retracted.

MODEL Number	MOUNTING Height	RETRACTED Height	USED WITH Caster Size	WEIGHT (POUND)
FL-LK-4E	5 ⁵ /8"	4 ⁷ /8"	4"	5
FL-LK-5EG	7"	6"	5"	5
FL-LK-5X	55/8"	4½"	5"	9
FL-LK-6EH	8"	7"	6"	7
FL-LK-6EM	7½"	63/4"	6"	5
FL-LK-6EL	71/4"	61/2"	6"	5
FL-LK-7X	71/4"	61/4"	6"	11
FL-LK-7G	7¾"	61/4"	6"	11
FL-LK-8EH	10½"	91/2"	8"	8
FL-LK-8EM	101/8"	91/2"	8"	5
FL-LK-8EL	9½"	8¾"	8"	5
FL-LK-10	915/16"	87/8"	8"	16
FL-LK-S	83/16"	7"	6"	6
FL-LK-SMR-L	10" / 13 ⁷ / ₈ "	15 ¹⁵ /16"	(2" of Travel)	9
FL-LK-SMR-R	10" / 13 ⁷ / ₈ "	15 ¹⁵ /16"	(2" of Travel)	9
STAINLESS STEEL CONSTR	UCTION			
FL-LK-SMR-SS-L	10" / 13 ⁷ / ₈ "	15 ¹⁵ / ₁₆ "	(2" of Travel)	9
FL-LK-SMR-SS-R	10" / 13 ⁷ /8"	15 ¹⁵ /16"	(2" of Travel)	9







model FL-LKL-5

Polyurethane Floor Locks

Floor Locks are ideal for maintenance and construction facilities. These floor locks are designed to create a stable environment, while decreasing the chance of jostling or slight movement. They are constructed of steel with a thermoplastic polyurethane base. To use, place the unit close to a desired wheel or caster and raise until tension is built. Once secured, a simple locking device can be activated by applying pressure to the foot pedal.

MODEL Number	RETRACTED Height	EXTENDED Height	USED WITH Caster Size	WEIGHT (POUND)
FL-LKH-4	4 ⁵ / ₈ "	53/4"	4"	4
FL-LKH-5	55/8"	63/4"	5"	5
FL-LKH-6	69/16"	7 ⁵ /8"	6"	5
FL-LKH-8	85/16"	97/16"	8"	5
FL-LKL-3	37/16"	41/4"	3"	2
FL-LKL-4	43/8"	51/4"	4"	2
FL-LKL-5	55/8"	61/4"	5"	2



model FL-LK-10