

# MANHOLE COVER LIFT PRODUCTS

## HD MANHOLE COVER LIFT SYSTEM



The Heavy Duty (HD) manhole cover lift dolly and Magnet & Dolly Combination system take several key features of our regular manhole cover lift system and adds an extra telescoping handle, giving you more leverage when lifting manhole covers.

Description	Wt. (lbs)	Model No.
Steel dolly, 12" Wheels, Hook Extension, 3pc telescoping Handle	58	MCL2000W12HD
All the above plus a PNL1600 On/Off PowerLift® magnet	58 + 51	MCL2W12HDPNL16



## POWERARM™ - VEHICLE MOUNTED

The Manhole PowerArm™ makes lifting and replacing manhole covers the most ergonomic. Great for repetitive access like survey/cleaning crews. Electric Hoist: drive within 3 feet of the center of the lid and let the "Arm" adjust to your location. This "Arm" has a 3-foot, 180° swing radius that allows the positioning of the magnet to the center of the manhole cover. Manual Hoist: Use backup camera to get as close to center as possible. Both "Arms" have 400 lbs. lifting capacity, fit into a standard 2" square receiver hitch and are constructed of welded tubular steel. (Rare Earth Magnet sold separately). Use PowerArm™ to lower items such as camera tractors, large sewer nozzles, pipe plugs, etc.

### ELECTRIC HOIST SPECIFICATIONS:

- » 55 AMP, 12 VDC with power-up & power-down control, removable
- » 16' remote control cord and a 20' galvanized cable with latch hook
- » Provided with a 2-Pole DC power connector, heavy-gauge 13' lead to connect hoist to vehicle battery (+) positive terminal and 6' long ground cable to connect to vehicle frame

### MANUAL HOIST SPECIFICATIONS:

- » Worm Gear hoist that will hold load when handle is released
- » Polyester strap with Zinc-plated hook & safety latch
- » Remove hoist, insert sideways for tailgate access, storage, and travel



Winch Type	A (in)	B (in)	C (in)	Weight (lbs)	Model No.
Electric	56-3/8	17-13/16	7-1/4	87	MCLPAE2000
Manual	30-7/8	20-1/2	20-13/16	30	MCLPAM1000

