


 model
SSSC Series

 model
CART-550-SS

Scissor Carts

Our fully welded Model SSSC carts resist corrosion in wet environments. All parts are made from 304 grade stainless steel, including the hydraulic pump and foot pedal. These carts are suitable for most food, medical, and pharmaceutical industry settings. Also suitable for wash-down applications. Two (2) rigid and two (2) swivel polyurethane wheels with brakes standard. Units feature a high quality actuated, single-speed hydraulic pump.

Models CART-550-SS & CART-1100-SS, two-speed hydraulic pump.

MODEL NUMBER	PLATFORM SIZE (W x L)	SERVICE RANGE	UNIFORM CAPACITY	WEIGHT (POUND)
SSSC-200	17 ³ / ₄ " x 27 ¹ / ₂ "	10" to 30 ¹ / ₂ "	200 lb.	135
SSSC-400	19 ¹ / ₂ " x 32 ³ / ₄ "	12 ³ / ₄ " to 36 ¹ / ₂ "	400 lb.	209
SSSC-1000	20 ¹ / ₂ " x 40"	17" to 40"	1,000 lb.	313
CART-550-SS*	19 ¹ / ₂ " x 31 ¹ / ₂ "	9 ³ / ₄ " to 33 ¹ / ₂ "	550 lb.	179
CART-600-D-SS*	23 ⁵ / ₈ " x 35 ¹ / ₂ "	13 ³ / ₈ " to 56 ¹ / ₄ "	600 lb.	340
CART-800-D-SS*	23 ⁵ / ₈ " x 35 ¹ / ₂ "	13 ³ / ₈ " to 48 ⁷ / ₁₆ "	800 lb.	335
CART-1100-SS*	23 ¹ / ₂ " x 35 ¹ / ₂ "	13" to 38 ¹ / ₂ "	1,100 lb.	249

*FOOT PUMP PEDAL, PUMP ASSEMBLY, AND HYDRAULIC CYLINDER ARE CHROME PLATED. REST OF THE UNIT IS FULLY STAINLESS STEEL.


 model
CART-200-D-PSS

 model
CART-1000-PSS

Hydraulic Elevating Carts (partially stainless steel)

Portable work positioning lift table is constructed of durable stainless steel to lift, position and transport heavy loads in corrosive environments, such as in lab, food service and healthcare applications. Durable stainless steel platform and frame with zinc plated scissor legs and pump assembly offers maximum rust-resistance. Foot-operated hydraulic pump raises platform. To lower unit use the hand-operated release. Cart rolls smoothly with poly-on-poly casters.

MODEL NUMBER	PLATFORM SIZE (W x L)	UNIFORM CAPACITY	SERVICE RANGE	FOOT PUMP SPEED	WEIGHT (POUND)
CART-200-D-PSS	17 ¹ / ₂ " x 27 ¹ / ₂ "	220 lb.	10" to 51"	SINGLE	158
CART-400-PSS	17 ¹ / ₂ " x 27 ¹ / ₂ "	400 lb.	8 ³ / ₄ " to 29"	SINGLE	149
CART-750-PSS	19 ³ / ₄ " x 32 ¹ / ₂ "	750 lb.	15 ¹ / ₂ " to 35 ¹ / ₂ "	SINGLE	202
CART-800-D-PSS	20" x 35 ¹ / ₂ "	800 lb.	15 ¹ / ₂ " to 50 ³ / ₄ "	SINGLE	275
CART-1000-PSS	19 ³ / ₄ " x 32 ¹ / ₂ "	1,000 lb.	15 ¹ / ₂ " to 35 ¹ / ₂ "	SINGLE	222
CART-1000-LD-PSS*	31 ¹ / ₂ " x 63"	1,000 lb.	15" to 36"	SINGLE	314
CART-1500-D-TS-PSS*	24" x 47 ¹ / ₂ "	1,500 lb.	19" to 68"	TWO	540
CART-1750-PSS*	20" x 39 ¹ / ₂ "	1,750 lb.	17" to 40"	SINGLE	288
CART-2000-PSS*	24" x 47"	2,000 lb.	15" to 39"	TWO	395

*PLATFORM, HANDLE, BASE FRAME, CASTER RIG, & HARDWARE ARE ALL STAINLESS STEEL. PUMP ASSEMBLY, SCISSOR LEGS, AND FOOT PEDAL ARE ZINC PLATED.


 model
CART-500-SCL-PSS


Scissor Cart with Built-In Scale (partially stainless steel)

Ideal for parts counting, inventory rooms, or shipping weights at the loading dock. Provides an ergonomic workstation while sitting or standing. Portable elevating platform includes an integral scale that provides an ergonomic weigh-station while sitting or standing. Digital scale readout features a Tare feature, displays weight in 1 lb. intervals, and is powered with over the counter batteries or AC adapter. Foot operated pump raises platform and a hand-operated knob lowers platform. Cart rolls smoothly on two (2) rigid and two (2) swivel with brakes poly-on-poly casters.

MODEL NUMBER	PLATFORM SIZE (W x L)	UNIFORM CAPACITY	LOWERED HEIGHT	RAISED HEIGHT	WEIGHT (POUND)
CART-500-SCL-PSS	19 ¹ / ₂ " x 32"	500 lb.	14"	38"	282

PLATFORM HANDLE, BASE FRAME CASTER RIG & HARDWARE ARE STAINLESS STEEL. PUMP ASSEMBLY, SCISSOR LEGS, AND FOOT PEDAL ARE ZINC PLATED


 model
AIR-1000-PSS

 model
AIR-1500-D-PSS

Air Hydraulic Carts (partially stainless steel)

Features two (2) speed foot pump and hand held reciprocating air/oil power to raise the platform. Utilize the two (2) speed foot pump for minor height adjustments and the factory air/oil power for effortless lifting of up to 2,000 uniform pounds. The platform, handle, base frame, caster brackets, and hardware are all stainless steel. Air pump, hydraulic cylinder, scissor legs, and foot pedal are zinc plated. Wheels are poly-on-poly.

MODEL NUMBER	PLATFORM SIZE (W x L)	UNIFORM CAPACITY	SERVICE RANGE	CASTER SIZE	WEIGHT (POUND)
AIR-800-D-PSS	20" x 35 ¹ / ₂ "	800 lb.	13 ³ / ₄ " to 51"	5" x 1 ¹ / ₂ "	317
AIR-1000-PSS	19 ¹¹ / ₁₆ " x 32 ¹ / ₂ "	1,000 lb.	15 ³ / ₄ " to 35 ⁷ / ₁₆ "	5" x 1 ¹ / ₂ "	340
AIR-1000-LD-PSS	31 ¹ / ₂ " x 63"	1,000 lb.	12 ¹ / ₈ " to 35 ¹ / ₂ "	5" x 1 ¹ / ₂ "	340
AIR-1500-D-PSS	24" x 47 ¹ / ₄ "	1,500 lb.	19 ¹ / ₂ " to 67"	6" x 1 ¹ / ₂ "	586
AIR-1750-PSS	20" x 39 ¹ / ₂ "	1,750 lb.	14 ¹ / ₄ " to 39 ¹ / ₂ "	6" x 1 ¹ / ₂ "	312
AIR-2000-PSS	24" x 47 ¹ / ₄ "	2,000 lb.	15" to 39 ¹ / ₂ "	6" x 1 ¹ / ₂ "	441