



model
L-270-DC-HD-SS

Tote Lifters HAND PUMP OR 12V DC

Designed to lift open bottom skids, boxes, and baskets. Two operations available: hand pump and 12V DC power with rocker switch to raise or lower. Hand pump design features an ergonomic pump handle with two lifting speeds to accommodate light or heavy loads. Side stabilizers lock lift in place when load is raised above 20½". DC power unit includes on-board battery charger. These stainless steel units feature nylon wheels. Units may not be suitable for wash down applications.

MODEL NUMBER	OPERATION	FORK SIZE (W x L)	SERVICE RANGE	UNIFORM CAPACITY	WEIGHT (POUND)
L-270-HD-SS [®]	HAND PUMP	26¾" x 45"	3½" to 31½"	2,000 lb.	310
L-270-DC-HD-SS [®]	12V DC	26¾" x 45"	3½" to 31½"	2,000 lb.	487



model
ULM-HTL-2149-20

High Tote Lifter 12V DC STANDARD

A High Tote Lifter is a perfect asset for any food handling atmosphere. The stainless steel construction is easily cleaned due to its smooth finish. An open fork design allows for simple inspection for overall complete hygiene. Products can be raised or lowered by utilizing the 12V DC powered hand pump. When the unit has been raised, it minimizes the amount of bending and twisting that can occur when products are placed in the improper height location. The wheeled scissor base creates a steady base when in position to load or unload merchandise. The overall compact design is easily stored when not in use.

MODEL NUMBER	OPERATION	FORK SIZE (W x L)	SERVICE RANGE	UNIFORM CAPACITY	WEIGHT (POUND)
ULM-HTL-2149-20	12V DC	21" x 45"	3¾" to 31½"	2,000 lb.	427



model
HYD-5-PSS

Hefti-Lifts

User-friendly portable stainless steel hydraulic lifts provide reliable, powerful lifting when moving and positioning loads. Includes removable platform for operations requiring forks (except HYD-10-DA-SS). Manual hydraulic foot pump yields ¾" of platform travel per stroke. Non-slip chain is used for accurate positioning. Units roll easily on two rigid and two swivel poly-on-steel casters and include a foot operated brake. Not for use with pallets. Each fork is 4⅜"W x 2½"H, the fork length is the same as the platform length. Overall fork width is 22". Compact, lightweight stackers are capable of a smaller turning radius. Equipped with a built-in automatic load check valve for improved safety. Model HYD-5-SS features a hydraulic foot pump, while model HYD-10-DA-SS comes with a dual acting manual hydraulic hand pump.

MODEL NUMBER	PLATFORM SIZE (W x L)	SERVICE RANGE	UNIFORM CAPACITY	OPERATION	WEIGHT (POUND)
PARTIALLY STAINLESS STEEL					
HYD-5-PSS [®]	21" x 24"	6¼" to 45⅝"	450 lb.	FOOT PUMP	236
STAINLESS STEEL					
HYD-5-SS [®]	23⅞" x 21¼"	6¼" to 45⅝"	450 lb.	FOOT PUMP	230
HYD-10-DA-SS [®]	N/A	3⅞" x 59"	800 lb.	HAND PUMP	270

*OVERALL FORK WIDTH 22", LENGTH 20-7/8"

model
HYD-10-DA-SS



DC Powered Hefti-Lift 12V DC STANDARD

This DC powered, medium duty, stainless steel semi-electric lift is user friendly providing reliable, powerful lifting when moving and positioning loads. Ideal for working in confined spaces and eliminates manual handling problems and injuries. Includes a stainless steel removable platform for operations requiring forks. Robust design, 304 grade all stainless steel construction. Hydraulic cylinders (including the piston) are also manufactured from type 304 stainless steel. The stainless steel piston is very important for long-term durability in wash-down environments. This stainless steel lift is non-corrosive and is good for washdown and corrosive acids applications. Ideal for food, pharmaceutical, chemical, and clean room applications. Unit rolls easily on two (2) rigid and two (2) swivel poly-on-steel casters and includes a foot operated brake. Each fork is 4½"W x 2½"H. The fork length is the same as the platform length. Overall fork width is 22". Forks are adjustable to handle different size loads. Runs off one (1) 12V battery. Includes an integral battery charger, battery charge indicator, and an emergency on/off switch. Not for use with pallets.



model
HYD-10-DC-SS



MODEL NUMBER	PLATFORM SIZE (W x L)	SERVICE RANGE	OVERALL SIZE (W x L x H)	UNIFORM CAPACITY	WEIGHT (POUND)
HYD-10-DC-SS [®]	22" x 25¾"	3½" to 59"	24½" x 44" x 68"	880 lb.	257