

Lift-and-Dump Hydraulic Drum Dumpers 460V 3-PHASE STD

Lift-and-Dump Hydraulic Drum Dumpers are what you need to dump drums at variable heights. The HLD works similarly to the HDD, but includes a lift cylinder that allows you to dump at various heights. Features a four (4) push button pendant, which allows the operator full independent control of both lift height and the dump angle.



model HLD-116-10-P

MODEL NUMBER	DUMP HEIGHT (MIN / MAX)	ROTATION HEIGHT	LEVEL HEIGHT	UNIFORM CAPACITY	FRAME (W x L)	WEIGHT (POUND)
PORTABLE LIFT AND DUMP DRUM DUMPERS (40° DUMP ANGLE)						
HLD-94-10-P	48" / 94"	163"	87¾"	1,000 lb.	51" x 75¾"	1372
HLD-116-10-P	60" / 116"	194"	99¾"	1,000 lb.	51" x 82¾"	1460
HLD-94-15-P	48" / 94"	163"	87¾"	1,500 lb.	51" x 75¾"	1392
HLD-116-15-P	60" / 116"	194"	99¾"	1,500 lb.	51" x 82¾"	1525
STATIONARY LIFT AND DUMP DRUM DUMPERS (45° DUMP ANGLE)						
HLD-94-10-S	48" / 94"	163"	85⅞"	1,000 lb.	51" x 65½"	1341
HLD-116-10-S	60" / 116"	194"	97⅞"	1,000 lb.	51" x 72½"	1522
HLD-94-15-S	48" / 94"	163"	85⅞"	1,500 lb.	51" x 65½"	1454
HLD-116-15-S	60" / 116"	194"	97⅞"	1,500 lb.	51" x 72½"	1466
12V DC POWERED PORTABLE LIFT AND DUMP DRUM DUMPERS (40° DUMP ANGLE)						
HLD-94-10-P-DC	48" / 94"	163"	87¾"	1,000 lb.	51" x 75¾"	1432
HLD-116-10-P-DC	60" / 116"	194"	99¾"	1,000 lb.	51" x 82¾"	1526
HLD-94-15-P-DC	48" / 94"	163"	87¾"	1,500 lb.	51" x 75¾"	1452
HLD-116-15-P-DC	60" / 116"	194"	99¾"	1,500 lb.	51" x 82¾"	1585
12V DC POWERED STATIONARY LIFT AND DUMP DRUM DUMPERS (45° DUMP ANGLE)						
HLD-94-10-S-DC	48" / 94"	163"	85⅞"	1,000 lb.	51" x 65½"	1401
HLD-116-10-S-DC	60" / 116"	194"	97⅞"	1,000 lb.	51" x 72½"	1582
HLD-94-15-S-DC	48" / 94"	163"	85⅞"	1,500 lb.	51" x 65½"	1514
HLD-116-15-S-DC	60" / 116"	194"	97⅞"	1,500 lb.	51" x 72½"	1526
VOLTAGE OPTION						
HLD-24VDC	24V DC POWER OPTION					--




Drum & Bin Dumpers 12V DC POWERED

The 304L Stainless Steel Drum & Bin Dumpers are great for the 'clean' workplace as well as manufacturing facilities. The structure is designed of 304L stainless steel, including hydraulic cylinders as well as the piston, which promotes easy cleaning and long lasting strength. Push button functionality allows the user to move to a precise position and stop the movement completely, in an emergency, with the emergency switch. (1) 12V AGM battery is waterproof, making maintenance a breeze. The unit rolls easily on poly wheels, while traversing from area to area. Once folded, the unit becomes more compact for utilizing less storage space.



model ULM-PBT-DTC-10



model ULM-PBT-BTC-10

MODEL NUMBER	DESCRIPTION	DUMP HEIGHT	ROTATION HEIGHT	LEVEL HEIGHT	UNIFORM CAPACITY	WEIGHT (POUND)
ULM-PBT-DTC-10	DRUM DUMPER	51"	106"	51⅞"	660 lb.	504
ULM-PBT-BTC-10	BIN DUMPER	51"	106"	51⅞"	660 lb.	452

Hoist Mounted Drum Carrier/Rotators

Rotate and position a fully loaded 55 gallon steel drum with ease. Use with an overhead hoist or a fork truck. Fork pockets measure 5½"W x 1⅝"H usable. Features a chain crank that allows the operator to rotate 360° drums that are out of reach. Drums are held in place with a drum locking system. Meets OSHA 1910.179 requirements. *Model DCT-2000* features gear box operation.



model DCT-2000

model DCT-85



model DCT-75

MODEL NUMBER	ACCEPTABLE DRUM TYPES	ROTATION METHOD	UNIFORM CAPACITY	WEIGHT (POUND)
DCT-75	55 GALLON STEEL	15' CHAIN	800 lb.	145
DCT-85	55 GALLON STEEL	15' CHAIN	1,500 lb.	145
DCT-2000	55 GALLON STEEL	15' CHAIN	2,000 lb.	169
DCT-R-HC	HAND CRANK (IN PLACE OF PULL CHAIN)			1

DRUM MUST BE FULL TO ROTATE AT RATED CAPACITY

See page 291 for options to handle plastic and fiber drums.