



YouTube




SKID ONLY



NO PALLET

**TILT MASTER**  
Only 1½" of Reach!



SKID



PALLET

**TILT MASTER STRADDLE**  
Only 13½" of Reach!

## Multi-Purpose Tote Dumpers

12V DC STD, OPTIONS ON PG. 108

Collect, transport, and dump materials while saving time and reducing work related injuries. Ideal for schools, hospitals, commercial, and industrial applications. One person can easily and safely empty loads weighing up to 600 pounds. To use, roll the tote into dumper, secure tote in place, and depress the 24V hand control. The tote will rotate over 135° to dump contents. Dump time is approximately 25 seconds. Standard features: Two (2) 8" x 2" glass filled nylon front wheels, Two (2) 8" x 3" phenolic rear casters, floor lock, 12V DC power, hand pendant control on 8 foot coil cord, and one (1) MPT-1 polyethylene tote. To operate under full capacity, purchase model MPT-2.

MODEL NUMBER	DUMP HEIGHT	ROTATED HEIGHT	UNIFORM CAPACITY	OVERALL SIZE (W x L)	WEIGHT (POUND)
JMD-1000-48	48"	105¾"	600 lb.	57¼" x 65⅞"	1061
JMD-1000-60	60"	117¾"	600 lb.	57¼" x 65⅞"	1075
JMD-1000-72	72"	129¾"	600 lb.	57¼" x 65⅞"	1099
MPT-1	ADDITIONAL ½ CUBIC YARD POLYETHYLENE TOTE CAPACITY 200 LB. - OVERALL SIZE: 52½"W x 30¾"D x 41⅜"H				128
MPT-2	½ CUBIC YARD POLYETHYLENE TOTE CAPACITY 600 LB. - OVERALL SIZE: 52½"W x 30¾"D x 42⅝"H				200

## Tilt Master & Tilt Master Straddle

Lift and position filled tote boxes or baskets without the need of a fork truck or lift table using the newly designed heavy-duty Tilt Master. These 90° tilters will function as transporters by moving completed products from work station to work station without waiting for a fork truck.

A ergonomic handle comes standard for quick and easy maneuverability. Unit has a thin profile to allow the user to get as close to the load as possible. Units roll easily on 8" x 3" phenolic steering wheels. Floor lock standard on non PTDS units. Series TM is designed to be used with open bottom pallets or skids only. The Tilt Master Straddle units, series TMS, can be used with virtually any kind of container or pallet. Units come standard with a control on an 8 foot coil cord.

Three power options to choose from.

Suffix -AC is 115V, 1 phase power with a push-button hand control.

Suffix -DC and DC-PTDS includes one (1) 12V battery DC series, (2) 12V batteries DC-PTDS series, push-button hand control, on-board charger and battery charge indicator gauge.

Suffix -DC-FC includes one (1) 12V battery, foot control, on-board charger and battery charge indicator gauge.

Suffix -AIR features reciprocating air/oil power with a heel/toe foot treadle control.

MODEL NUMBER	POWER & CONTROL	UNIFORM CAPACITY	FORK ADJUSTMENT	OPERATOR REACH	FORK WIDTH	ROTATED HEIGHT	LOWERED HEIGHT	OVERALL SIZE (W x L x H)	WEIGHT (POUND)
<b>TILT MASTER</b>									
TM-20-AC	115V / 1PH HAND	2,000 lb.	Fixed @ 26" (OD)	7¼"	6"	33"	3⅝"	41" x 75⅞" x 28⅝"	646
TM-20-DC	12V DC HAND	2,000 lb.	Fixed @ 26" (OD)	7¼"	6"	33"	3⅝"	41" x 75⅞" x 28⅝"	767
TM-20-DC-FC	12V DC FOOT	2,000 lb.	Fixed @ 26" (OD)	7¼"	6"	33"	3⅝"	41" x 75⅞" x 28⅝"	772
TM-20-DC-PTDS	12V DC HAND**	2,000 lb.	Fixed @ 26" (OD)	7¼"	6"	33"	3⅝"	52" x 75⅞" x 54"	950
TM-20-AIR	AIR/OIL FOOT	2,000 lb.	Fixed @ 26" (OD)	7¼"	6"	33"	3⅝"	41" x 75⅞" x 28⅝"	621
TM-40-AC	115V / 1PH HAND	4,000 lb.	Fixed @ 26" (OD)	7¼"	6"	33"	3⅝"	41" x 75⅞" x 28⅝"	707
TM-40-DC	12V DC HAND	4,000 lb.	Fixed @ 26" (OD)	7¼"	6"	33"	3⅝"	41" x 75⅞" x 28⅝"	781
TM-40-DC-FC	12V DC FOOT	4,000 lb.	Fixed @ 26" (OD)	7¼"	6"	33"	3⅝"	41" x 75⅞" x 28⅝"	786
TM-40-DC-PTDS	12V DC HAND**	4,000 lb.	Fixed @ 26" (OD)	7¼"	6"	33"	3⅝"	52" x 75⅞" x 54"	964
TM-40-AIR	AIR/OIL FOOT	4,000 lb.	Fixed @ 26" (OD)	7¼"	6"	33"	3⅝"	41" x 75⅞" x 28⅝"	631
TM-60-AC	115V / 1PH HAND	6,000 lb.	Fixed @ 27" (OD)	7¼"	6**	33"	3⅝"	41" x 75⅞" x 28⅝"	739
TM-60-DC	12V DC HAND	6,000 lb.	Fixed @ 27" (OD)	7¼"	6**	33"	3⅝"	41" x 75⅞" x 28⅝"	777
TM-60-DC-PTDS	12V DC HAND**	6,000 lb.	Fixed @ 27" (OD)	7¼"	6"	33"	3⅝"	52" x 75⅞" x 54"	960
TM-60-AIR	AIR/OIL FOOT	6,000 lb.	Fixed @ 27" (OD)	7¼"	6**	33"	3⅝"	41" x 75⅞" x 28⅝"	851
<b>TILT MASTER STRADDLE</b>									
TMS-20-AC	115V / 1PH HAND	2,000 lb.	½" to 28½" (ID)	13½"	4"	37"	3"	57¼" x 72⅜" x 29¼"	989
TMS-20-DC	12V DC HAND	2,000 lb.	½" to 28½" (ID)	13½"	4"	37"	3"	57¼" x 72⅜" x 29¼"	1017
TMS-20-DC-PTDS	12V DC HAND**	2,000 lb.	½" to 28½" (ID)	13½"	4"	37"	3"	57¼" x 72⅜" x 54"	1200
TMS-20-AIR	AIR/OIL FOOT	2,000 lb.	½" to 28½" (ID)	13½"	4"	37"	3"	57¼" x 72⅜" x 29¼"	886
TMS-40-AC	115V / 1PH HAND	4,000 lb.	½" to 28½" (ID)	13½"	4"	37"	3"	57¼" x 72⅜" x 29¼"	953
TMS-40-DC	12V DC HAND	4,000 lb.	½" to 28½" (ID)	13½"	4"	37"	3"	57¼" x 72⅜" x 29¼"	1046
TMS-40-DC-PTDS	12V DC HAND**	4,000 lb.	½" to 28½" (ID)	13½"	4"	37"	3"	57¼" x 72⅜" x 54"	1229
TMS-40-AIR	AIR/OIL FOOT	4,000 lb.	½" to 28½" (ID)	13½"	4"	37"	3"	57¼" x 72⅜" x 29¼"	893
TMS-60-AC	115V / 1PH HAND	6,000 lb.	½" to 28½" (ID)	13½"	4"	37"	3"	57¼" x 72⅜" x 29¼"	978
TMS-60-DC	12V DC HAND	6,000 lb.	½" to 28½" (ID)	13½"	4"	37"	3"	57¼" x 72⅜" x 29¼"	1067
TMS-60-DC-PTDS	12V DC HAND**	6,000 lb.	½" to 28½" (ID)	13½"	4"	37"	3"	57¼" x 72⅜" x 54"	1250
TMS-60-AIR	AIR/OIL FOOT	6,000 lb.	½" to 28½" (ID)	13½"	4"	37"	3"	57¼" x 72⅜" x 29¼"	967
<b>OPTION</b>									
TM-CHUTE	RETROFIT CHUTE OPTION FOR BOTH TILT MASTER & TILT MASTER STRADDLE								18

\*6½" WITH STIFFENER

\*\*POWER TRACTION DRIVE (POWER DRIVE / POWER TILT)