

## Maintenance Ladders

Portable ladders for use around warehouses, hardware stores, or inventory rooms. Tilt the unit to allow for portability. Units roll on 4" poly-on-poly wheels. Constructed of square tubing framework, which handles uniform capacities up to 350 pounds. Features 30" high removable hand railing (36" on 12 step models), access chain, 21" deep top platform, and baked-in powder-coated toughness. Each step measures 24" wide by 7" deep and is spaced 10" apart. Models with 5 - 12 steps are shipped crated, some assembly required. Complies with ANSI A14.7 and OSHA 1910.29 specifications.



model LAD-MM-6-G

NO. OF STEPS	TOP STEP HEIGHT	OVERALL (W x D x H)	WEIGHT (POUND)	MODEL NUMBER GRIP STRUT	MODEL NUMBER PERFORATED
2	20"	29½" x 38½" x 50"	110	LAD-MM-2-G	LAD-MM-2-P
3	30"	29½" x 38½" x 60"	118	LAD-MM-3-G	LAD-MM-3-P
4	40"	29½" x 43⅝" x 70"	125	LAD-MM-4-G	LAD-MM-4-P
5	50"	29½" x 49¾" x 80"	180	LAD-MM-5-G	LAD-MM-5-P
6	60"	29½" x 56⅜" x 90"	210	LAD-MM-6-G	LAD-MM-6-P
7	70"	29½" x 62⅜" x 100"	243	LAD-MM-7-G	LAD-MM-7-P
8	80"	29½" x 68⅝" x 110"	260	LAD-MM-8-G	LAD-MM-8-P
9	90"	29½" x 74⅞" x 120"	279	LAD-MM-9-G	LAD-MM-9-P
10	100"	32" x 81⅞" x 130"	310	LAD-MM-10-G	LAD-MM-10-P
11	110"	32" x 87⅞" x 140"	334	LAD-MM-11-G	LAD-MM-11-P
12	120"	32" x 93¼" x 156"	366	LAD-MM-12-G	LAD-MM-12-P

## Modular Style Stairways

Attractive Modular Style Stairways are economical and easily assembled. Steps are 36" wide with non-skid grip strut, which bolt in place and are baked-in powder-coated toughness. Standard climb angle is 31°. Customer must provide their landing height at time of purchase. Handrails and side rails bolt together. The handrail tubing has a powder-coat yellow finish. Units meet OSHA requirements and unit ships disassembled. Concrete Anchoring Hardware available.



MODEL NUMBER	NUMBER OF STEPS	TOP STEP HEIGHT	UNIFORM CAPACITY	WEIGHT (POUND)
STAIR-36	5	36"	1,000 lb.	399
STAIR-48	6	48"	1,000 lb.	519
STAIR-60	8	60"	1,000 lb.	528
STAIR-72	10	72"	1,000 lb.	592
STAIR-84	12	84"	1,000 lb.	734
STAIR-96	13	96"	1,000 lb.	898
STAIR-108	15	108"	1,000 lb.	954
STAIR-120	16	120"	1,000 lb.	1004
STAIR-132	18	132"	1,000 lb.	1145
STAIR-144	20	144"	1,000 lb.	1190

## Modular Steel Work Platform Systems

Modular Work Platform Systems can be configured to fit any application. Platform legs have a fixed height and provide stability to the entire modular unit. Designed for maximum loading capacity of 500 pounds. Stair / platform configuration has a maximum capacity of 1,000 pounds. Fixed height ladder sections attach to platform. Individual grip steps are 23⅞" wide by 7" deep with 10" step spacing. Each ladder section includes round tube handrails. Each handrail section has a midrail and 4" toeboard. Constructed of industrial grade welded steel with a powder-coat finish. Meets OSHA specification 1910.23. Hardware is included for easy assembly. Concrete wedge anchors available for securing unit to floor. All components are sold separately. Survey sheet available on page 248.



MODEL NUMBER	DESCRIPTION	PLATFORM HEIGHT	WEIGHT (POUND)
MP-S-2	Stair Step Section with Handrails, 2 steps	30"	102
MP-S-3	Stair Step Section with Handrails, 3 steps	40"	117
MP-S-4	Stair Step Section with Handrails, 4 steps	50"	154
MP-S-5	Stair Step Section with Handrails, 5 steps	60"	187
MP-S-6	Stair Step Section with Handrails, 6 steps	70"	211
MP-P	Fixed-Height Platform 36" x 36" - no handrail	10"	66
MP-L-2	Fixed-Height Platform Support Legs - one pair	30"	33
MP-L-3	Fixed-Height Platform Support Legs - one pair	40"	49
MP-L-4	Fixed-Height Platform Support Legs - one pair	50"	65
MP-L-5	Fixed-Height Platform Support Legs - one pair	60"	81
MP-L-6	Fixed-Height Platform Support Legs - one pair	70"	99
MP-HR	Handrail with Toeboard, 36"L x 42"H, sold each		75
AS-383	3/8" x 3"L Concrete Wedge Anchor, sold each		1
AS-383-4PK	3/8" x 3"L Concrete Wedge Anchor, 4 pack		4



model MP-L-4



model MP-HR



model MP-P