


## Lift Master Booms

Unique performance, convenience, and safety features are built into every Lift Master Boom. Fabricated from structural steel with welding to meet AWS creates a rugged and durable boom that will provide long term service. Telescopic units come with an infinitely adjustable locking screw (except orbit booms which feature a locking detent). Fork pockets for 4,000 pound uniform capacity models measure 7½"W x 2½"H usable on 24" centers. Usable fork pockets are 7¼"W x 2¼"H for 6,000 and 8,000 pound uniform capacity models. Optional fork pocket centers available, contact factory. A safety restraint secures the boom to the fork truck for safe operation. Each unit includes two lifting hooks.



**ORBITING BOOM**  
model LM-OBT-4-24



**LIFT MASTER BOOM**  
model LM-1T-4-36



**ECONOMY BOOM**  
model LM-EBT-4-24



**FIXED 15° BOOM**  
model LM-F15-4-24



**HIGH-RISE BOOM**  
model LM-HRNT-4-24



**LIFT MASTER BOOM**  
model LM-1T-8-24



**NON-TELESCOPING ECONOMY BOOM**  
model LM-EBNT-4-24



**SHORTY BOOM**  
model LMS-EBT-46-8



**NON-TELESCOPING SHORTY BOOM**  
model LMS-EBNT-40-4

MODEL NUMBER	DESCRIPTION	OVERALL HEIGHT	OVERALL EXTENDED LENGTH	UNIFORM CAPACITY	WEIGHT (POUND)
<b>TELESCOPING STYLE</b>					
LM-1T-4-24	LIFT MASTER BOOM	25 <sup>7</sup> / <sub>8</sub> "	151 <sup>1</sup> / <sub>4</sub> "	4,000 lb.	425
LM-OBT-4-24	ORBIT BOOM	27 <sup>11</sup> / <sub>16</sub> "	146 <sup>5</sup> / <sub>8</sub> "	4,000 lb.	433
LM-HRT-4-24	HIGH-RISE BOOM	79 <sup>13</sup> / <sub>16</sub> "	92 <sup>5</sup> / <sub>8</sub> "	4,000 lb.	950
LM-EBT-4-24	ECONOMY BOOM	13 <sup>1</sup> / <sub>2</sub> "	151 <sup>1</sup> / <sub>2</sub> "	4,000 lb.	333
LM-F15-4-24	FIXED 15 DEGREES	33"	147"	4,000 lb.	370
LM-1T-6-24	LIFT MASTER BOOM	25 <sup>7</sup> / <sub>8</sub> "	151 <sup>1</sup> / <sub>4</sub> "	6,000 lb.	480
LM-OBT-6-24	ORBIT BOOM	27 <sup>11</sup> / <sub>16</sub> "	146 <sup>5</sup> / <sub>8</sub> "	6,000 lb.	476
LM-HRT-6-24	HIGH-RISE BOOM	79 <sup>13</sup> / <sub>16</sub> "	92 <sup>5</sup> / <sub>8</sub> "	6,000 lb.	950
LM-EBT-6-24	ECONOMY BOOM	13 <sup>1</sup> / <sub>2</sub> "	151 <sup>1</sup> / <sub>2</sub> "	6,000 lb.	377
LM-1T-8-24	LIFT MASTER BOOM	26 <sup>9</sup> / <sub>16</sub> "	149 <sup>1</sup> / <sub>8</sub> "	8,000 lb.	647
LM-OBT-8-24	ORBIT BOOM	28 <sup>7</sup> / <sub>8</sub> "	148 <sup>1</sup> / <sub>2</sub> "	8,000 lb.	622
LM-EBT-8-24	ECONOMY BOOM	15"	149 <sup>3</sup> / <sub>8</sub> "	8,000 lb.	577
<b>NON-TELESCOPING STYLE</b>					
LM-1NT-4-24	LIFT MASTER BOOM	24 <sup>13</sup> / <sub>16</sub> "	81 <sup>1</sup> / <sub>2</sub> "	4,000 lb.	333
LM-OBNT-4-24	ORBIT BOOM	26 <sup>5</sup> / <sub>8</sub> "	80 <sup>7</sup> / <sub>8</sub> "	4,000 lb.	337
LM-HRNT-4-24	HIGH-RISE BOOM	78 <sup>9</sup> / <sub>16</sub> "	50 <sup>3</sup> / <sub>8</sub> "	4,000 lb.	810
LM-EBNT-4-24	ECONOMY BOOM	13 <sup>5</sup> / <sub>16</sub> "	81 <sup>5</sup> / <sub>8</sub> "	4,000 lb.	258
LM-1NT-6-24	LIFT MASTER BOOM	24 <sup>13</sup> / <sub>16</sub> "	81 <sup>1</sup> / <sub>2</sub> "	6,000 lb.	489
LM-OBNT-6-24	ORBIT BOOM	26 <sup>5</sup> / <sub>8</sub> "	80 <sup>7</sup> / <sub>8</sub> "	6,000 lb.	391
LM-HRNT-6-24	HIGH-RISE BOOM	78 <sup>9</sup> / <sub>16</sub> "	50 <sup>3</sup> / <sub>8</sub> "	6,000 lb.	697
LM-EBNT-6-24	ECONOMY BOOM	13 <sup>15</sup> / <sub>16</sub> "	81 <sup>5</sup> / <sub>8</sub> "	6,000 lb.	291
LM-1NT-8-24	LIFT MASTER BOOM	23 <sup>1</sup> / <sub>2</sub> "	80 <sup>1</sup> / <sub>8</sub> "	8,000 lb.	476
LM-OBNT-8-24	ORBIT BOOM	25 <sup>1</sup> / <sub>8</sub> "	79 <sup>1</sup> / <sub>2</sub> "	8,000 lb.	792
LM-EBNT-8-24	ECONOMY BOOM	11 <sup>1</sup> / <sub>2</sub> "	80 <sup>3</sup> / <sub>8</sub> "	8,000 lb.	418

LARGER FORK POCKETS 7"W x 3"H (inside dimensions), model LM-FP-37

LARGER FORK POCKETS 9"W x 3"H (inside dimensions), model LM-FP-39

## Shorty Lift Master Booms

Short boom length is ideal for tight areas. Choose either telescoping or non-telescoping design. Includes built-in fork pockets, safety restraint, and two lifting hooks. Overall width is 32". Steel construction.

MODEL NUMBER	DESCRIPTION	OVERALL HEIGHT	OVERALL LENGTH	UNIFORM CAPACITY	WEIGHT (POUND)
LMS-EBT-46-4	TELESCOPING	13 <sup>1</sup> / <sub>2</sub> "	55 <sup>1</sup> / <sub>4</sub> " to 93"	4,000 lb.	248
LMS-EBT-46-6	TELESCOPING	13 <sup>1</sup> / <sub>2</sub> "	55 <sup>1</sup> / <sub>4</sub> " to 93"	6,000 lb.	296
LMS-EBT-46-8	TELESCOPING	15"	53 <sup>7</sup> / <sub>8</sub> " to 90 <sup>7</sup> / <sub>8</sub> "	8,000 lb.	430
LMS-EBNT-40-4	NON-TELESCOPING	13 <sup>5</sup> / <sub>16</sub> "	50 <sup>3</sup> / <sub>4</sub> "	4,000 lb.	214
LMS-EBNT-40-6	NON-TELESCOPING	13 <sup>5</sup> / <sub>16</sub> "	50 <sup>3</sup> / <sub>4</sub> "	6,000 lb.	244
LMS-EBNT-40-8	NON-TELESCOPING	11 <sup>1</sup> / <sub>2</sub> "	49 <sup>3</sup> / <sub>8</sub> "	8,000 lb.	320