


Lift Master Booms

Unique performance, convenience, and safety features are built into every Lift Master Boom. Fabricated from structural steel with welding to meet AWS creates a rugged and durable boom that will provide long term service. Telescopic units come with an infinitely adjustable locking screw (except orbit booms which feature a locking detent). Fork pockets for 4,000 pound uniform capacity models measure 7½"W x 2½"H usable on 24" centers. Usable fork pockets are 7¼"W x 2¼"H for 6,000 and 8,000 pound uniform capacity models. Optional fork pocket centers available, contact factory. A safety restraint secures the boom to the fork truck for safe operation. Each unit includes two lifting hooks.



ORBITING BOOM
model LM-OBT-4-24



LIFT MASTER BOOM
model LM-1T-4-36



ECONOMY BOOM
model LM-EBT-4-24



FIXED 15° BOOM
model LM-F15-4-24



HIGH-RISE BOOM
model LM-HRNT-4-24



LIFT MASTER BOOM
model LM-1T-8-24



NON-TELESCOPING ECONOMY BOOM
model LM-EBNT-4-24



SHORTY BOOM
model LMS-EBT-46-8



NON-TELESCOPING SHORTY BOOM
model LMS-EBNT-40-4

MODEL NUMBER	DESCRIPTION	OVERALL HEIGHT	OVERALL EXTENDED LENGTH	UNIFORM CAPACITY	WEIGHT (POUND)
TELESCOPING STYLE					
LM-1T-4-24	LIFT MASTER BOOM	25 ⁷ / ₈ "	151 ¹ / ₄ "	4,000 lb.	425
LM-OBT-4-2	ORBIT BOOM	27 ¹¹ / ₁₆ "	146 ⁵ / ₈ "	4,000 lb.	433
LM-HRT-4-24	HIGH-RISE BOOM	79 ¹³ / ₁₆ "	92 ⁵ / ₈ "	4,000 lb.	950
LM-EBT-4-24	ECONOMY BOOM	13 ¹ / ₂ "	151 ¹ / ₂ "	4,000 lb.	333
LM-F15-4-24	FIXED 15 DEGREES	33"	147"	4,000 lb.	370
LM-1T-6-24	LIFT MASTER BOOM	25 ⁷ / ₈ "	151 ¹ / ₄ "	6,000 lb.	480
LM-OBT-6-24	ORBIT BOOM	27 ¹¹ / ₁₆ "	146 ⁵ / ₈ "	6,000 lb.	476
LM-HRT-6-24	HIGH-RISE BOOM	79 ¹³ / ₁₆ "	92 ⁵ / ₈ "	6,000 lb.	950
LM-EBT-6-24	ECONOMY BOOM	13 ¹ / ₂ "	151 ¹ / ₂ "	6,000 lb.	377
LM-1T-8-24	LIFT MASTER BOOM	26 ⁹ / ₁₆ "	149 ¹ / ₈ "	8,000 lb.	647
LM-OBT-8-24	ORBIT BOOM	28 ⁷ / ₈ "	148 ¹ / ₂ "	8,000 lb.	622
LM-EBT-8-24	ECONOMY BOOM	15"	149 ³ / ₈ "	8,000 lb.	577
NON-TELESCOPING STYLE					
LM-1NT-4-24	LIFT MASTER BOOM	24 ¹³ / ₁₆ "	81 ¹ / ₂ "	4,000 lb.	333
LM-OBNT-4-24	ORBIT BOOM	26 ⁵ / ₈ "	80 ⁷ / ₈ "	4,000 lb.	337
LM-HRNT-4-24	HIGH-RISE BOOM	78 ⁹ / ₁₆ "	50 ³ / ₈ "	4,000 lb.	810
LM-EBNT-4-24	ECONOMY BOOM	13 ⁵ / ₁₆ "	81 ⁵ / ₈ "	4,000 lb.	258
LM-1NT-6-24	LIFT MASTER BOOM	24 ¹³ / ₁₆ "	81 ¹ / ₂ "	6,000 lb.	489
LM-OBNT-6-24	ORBIT BOOM	26 ⁵ / ₈ "	80 ⁷ / ₈ "	6,000 lb.	391
LM-HRNT-6-24	HIGH-RISE BOOM	78 ⁹ / ₁₆ "	50 ³ / ₈ "	6,000 lb.	697
LM-EBNT-6-24	ECONOMY BOOM	13 ¹⁵ / ₁₆ "	81 ⁵ / ₈ "	6,000 lb.	291
LM-1NT-8-24	LIFT MASTER BOOM	23 ¹ / ₂ "	80 ¹ / ₈ "	8,000 lb.	476
LM-OBNT-8-24	ORBIT BOOM	25 ¹ / ₈ "	79 ¹ / ₂ "	8,000 lb.	792
LM-EBNT-8-24	ECONOMY BOOM	11 ¹ / ₂ "	80 ³ / ₈ "	8,000 lb.	418

LARGER FORK POCKETS 7"W x 3"H (inside dimensions), model LM-FP-37

LARGER FORK POCKETS 9"W x 3"H (inside dimensions), model LM-FP-39

Shorty Lift Master Booms

Short boom length is ideal for tight areas. Choose either telescoping or non-telescoping design. Includes built-in fork pockets, safety restraint, and two lifting hooks. Overall width is 32". Steel construction.

MODEL NUMBER	DESCRIPTION	OVERALL HEIGHT	OVERALL LENGTH	UNIFORM CAPACITY	WEIGHT (POUND)
LMS-EBT-46-4	TELESCOPING	13 ¹ / ₂ "	55 ¹ / ₄ " to 93"	4,000 lb.	248
LMS-EBT-46-6	TELESCOPING	13 ¹ / ₂ "	55 ¹ / ₄ " to 93"	6,000 lb.	296
LMS-EBT-46-8	TELESCOPING	15"	53 ⁷ / ₈ " to 90 ⁷ / ₈ "	8,000 lb.	430
LMS-EBNT-40-4	NON-TELESCOPING	13 ⁵ / ₁₆ "	50 ³ / ₄ "	4,000 lb.	214
LMS-EBNT-40-6	NON-TELESCOPING	13 ⁵ / ₁₆ "	50 ³ / ₄ "	6,000 lb.	244
LMS-EBNT-40-8	NON-TELESCOPING	11 ¹ / ₂ "	49 ³ / ₈ "	8,000 lb.	320