

## Tank Access Ladders

The NTAL Tank Access Ladders have a unique modular design for inspecting storage tanks. The rungs are offset to protect knuckles and are made from non-slip steel material. This ladder has a durable welded steel construction and a baked-in powder-coated toughness. Uniform capacity is 300 pounds. Models with 10 to 15 rungs ship knockdown.



MODEL NUMBER	OVERALL HEIGHT (FT.)	NUMBER OF RUNGS	OVERALL WIDTH	USABLE WIDTH	WEIGHT (POUND)
NTAL-7	7	7	14"	13"	69
NTAL-10	10	10	14"	13"	128
NTAL-12	12	12	14"	13"	138
NTAL-15	15	15	14"	13"	148



model NTAL-7



## Walk-Thru Style Dock Ladders

Prevent needless dock injuries with Walk-Thru Style Dock Ladders. Constructed of steel pipe. Mount ladder directly to the dock face by either welding or bolting on. The top half of each step is covered with a slip resistant material for extra safety during climbing and descending of the ladder. The extra high handrail provides maximum assistance and safety. All ladders project 8 $\frac{3}{8}$ " out from face of dock. Uniform capacity is 300 pounds. Models with 5 - 10 steps ship knockdown. Some assembly required. Baked-in powder-coated toughness.

MODEL NUMBER	OVERALL SIZE (W x H)	NUMBER OF RUNGS	TOP STEP HEIGHT	WIDTH OF STEP	DISTANCE BETWEEN STEP	WEIGHT (POUND)
DKL-2	20 $\frac{7}{16}$ " x 65 $\frac{1}{2}$ "	2	15"	18"	12"	86
DKL-3	20 $\frac{7}{16}$ " x 77 $\frac{1}{2}$ "	3	27"	18"	12"	89
DKL-4	20 $\frac{7}{16}$ " x 89 $\frac{1}{2}$ "	4	39"	18"	12"	92
DKL-5	20 $\frac{7}{16}$ " x 101 $\frac{1}{2}$ "	5	51"	18"	12"	96
DKL-6	20 $\frac{7}{16}$ " x 113 $\frac{1}{2}$ "	6	63"	18"	12"	98
DKL-7	20 $\frac{7}{16}$ " x 125 $\frac{1}{2}$ "	7	75"	18"	12"	118
DKL-8	20 $\frac{7}{16}$ " x 137 $\frac{1}{2}$ "	8	87"	18"	12"	121
DKL-9	20 $\frac{7}{16}$ " x 149 $\frac{1}{2}$ "	9	99"	18"	12"	123
DKL-10	20 $\frac{7}{16}$ " x 161 $\frac{1}{2}$ "	10	111"	18"	12"	148



model DKL-4

## Aluminum Telescopic Ladders

Ideal when storage space is limited. The lightweight and low profile design allows for storage in closets or tight spaces. Each step is serrated and has a spring loaded locking pin that automatically engages to secure step height. The release mechanism provides a smooth automatic closing design. These ladders extend in 12" increments. Top bumper guards and molded rubber feet protect walls and floors against scratches. Meets OSHA and ANSI specifications.



model TLAD-10



model TLAD-12



model TLAD-12-1A



model TLAD-15-1

MODEL NUMBER	TOP STEP HEIGHT	CLOSED SIZE (W x D x H)	STEP DEPTH	UNIFORM CAPACITY	WEIGHT (POUND)
TLAD-10	6 in. - 10 ft.	18 $\frac{1}{2}$ " x 2 $\frac{3}{4}$ " x 29"	1 $\frac{1}{2}$ "	225 lb.	24
TLAD-12	6 in. - 12 ft.	19 $\frac{1}{4}$ " x 3 $\frac{1}{2}$ " x 32"	1 $\frac{1}{2}$ "	225 lb.	30
TLAD-12-1A	6 in. - 12 ft.	18" x 4" x 32"	1 $\frac{1}{2}$ "	300 lb.	36
TLAD-15-1	6 in. - 15 ft.	19" x 4" x 36"	1 $\frac{1}{2}$ "	250 lb.	40

