

## Electric Pallet Truck 24V DC STANDARD

A 304L Stainless Steel Electric Pallet Truck is an ideal supplement to food service and other sterile settings. The 304L stainless steel construction, including hydraulic cylinders as well as the piston, provides not only a strong structure for transferring heavy loads between work areas, but is also easily washable. An enclosed shelter for electronic components that is simple to access for general upkeep, while the humidity resistant electronics are great for working in difficult conditions. The adjustable height handle with built in horn helps maintain an ergonomic posture of the user during use. The emergency stop is perfectly located near the driving position of the unit for a rapid shut-down in the case of a crisis. During use the unit maneuvers efficiently on its waterproof roll wheels. Unit comes standard in 304 Stainless Steel (316 Stainless Steel is an option, contact factory for pricing). Battery is 24V/240Ah



model  
ULM-EPT-2745-44

MODEL NUMBER	UNIFORM CAPACITY	OVERALL FORK SIZE (W x L)	SERVICE RANGE	OVERALL SIZE (W x L x H)	WEIGHT (POUND)
<b>ULM-EPT-2745-44</b>	4,400 lb.	27" x 44½"	3 <sup>3</sup> / <sub>8</sub> " to 7 <sup>5</sup> / <sub>8</sub> "	28" x 72" x 56"	1130

## DC Powered and Manual Scissor Carts (partially stainless steel)

Tables provide unparalleled ergonomic support in lifting, palletizing, loading, and unloading applications. Carts are raised or lowered with either a 12V DC powered motor or a manual two-speed auto-shift foot pump. Units roll smoothly with two (2) rigid and two (2) swivel 4" x 2" phenolic casters with brakes. Push handle is removable. Internal DC powered electric motor and one (1) 12V battery is included on DC units. Electric motor is rated at 1600 watts. Built-in battery charger is included (operated on 115V AC power). Push buttons to raise and lower lift are located on the power unit. Hand control on coil cord standard. Platform is equipped with perimeter pinch-point guard for OSHA compliance. Partially stainless steel tables include a stainless steel platform, base frame, and hydraulic cylinder. Scissor legs are galvanized.

MODEL NUMBER	PLATFORM SIZE (W x L)	SERVICE RANGE	UNIFORM CAPACITY	LIFT SPEED OR # OF PUMPS	WEIGHT (POUND)
<b>12V DC POWER</b>					
<b>CART-23-10-DC-PSS</b>	24" x 36"	11" to 33½"	1,000 lb.	14 sec.	578
<b>CART-23-15-DC-PSS</b>	24" x 36"	11" to 33½"	1,500 lb.	16 sec.	583
<b>TWO-SPEED FOOT PUMP</b>					
<b>CART-23-10-M-PSS</b>	24" x 36"	11" to 33½"	1,000 lb.	54 low - 27 high	424
<b>CART-23-15-M-PSS</b>	24" x 36"	11" to 33½"	1,500 lb.	54 low - 27 high	427



model  
CART-23-15-M-PSS



model  
CART-23-10-DC-PSS

## Mechanical Scissor Cart (partially stainless steel)

Raise and lower material quickly and easily with our Mechanical Scissor Cart. Cart rolls smoothly on two (2) rigid and two (2) swivel casters. Mechanical screw drive provides precise positioning with no downward drift. The platform, frame, handle, caster rigs, and hardware are all stainless steel. Crank assembly and scissor legs are zinc plated. Wheels are poly-on-poly.

MODEL NUMBER	PLATFORM SIZE (W x L)	UNIFORM CAPACITY	LOWERED HEIGHT	RAISED HEIGHT	WEIGHT (POUND)
<b>CART-660-M-PSS</b>	23½" x 37"	660 lb.	17¼"	39¼"	148



model  
CART-660-M-PSS

## Hydraulic Post Tables (partially stainless steel)

Foot-operated partially stainless steel Hydraulic Post Tables are built for heavy-duty shop use. They are good for many material handling uses including: lifting dies and castings, moving machine parts, positioning welders' work, leveling feed material for pump presses, conveyors and press brakes, and similar material handling jobs. Posts are telescoping to help stabilize and support loads during operation. Units include four (4) casters; two (2) locking swivel with brakes and two (2) rigid. Light-duty units feature a single-speed foot pump. Heavy-duty units feature a two-speed foot pump for maximum operator convenience. All foot pumps include a down speed control valve for safe platform lowering. Partially stainless steel tables include a stainless steel platform, base frame, handle, caster rigs, and hardware. Pump assembly and leg posts are zinc plated. Poly-on-Poly casters standard.



model  
HT-02-1616A-PSS



model  
HT-20-2436A-PSS

MODEL NUMBER	PLATFORM SIZE (W x L)	UNIFORM CAPACITY	SERVICE RANGE	NUMBER OF POSTS	CASTER SIZE/TYPE*	OPERATION	WEIGHT (POUND)
<b>HT-02-1616A-PSS</b>	16" x 16"	200 lb.	31" to 49"	--	4" x 1¼" PP	1-SPEED FOOT PUMP	126
<b>HT-05-1818A-PSS</b>	18" x 18"	500 lb.	31" to 49"	2	4" x 1¼" PP	1-SPEED FOOT PUMP	151
<b>HT-10-2036A-PSS</b>	20" x 36"	1,000 lb.	36" to 54"	2	4" x 1½" PP	2-SPEED FOOT PUMP	241
<b>HT-20-2436A-PSS</b>	24" x 36"	2,000 lb.	36" to 54"	4	5" x 1½" PP	2-SPEED FOOT PUMP	332
<b>HT-20-3036A-PSS</b>	30" x 36"	2,000 lb.	36" to 54"	4	5" x 1½" PP	2-SPEED FOOT PUMP	376

LOW PROFILE & SHORT PUMP LIFT RANGE AVAILABLE. CONSULT FACTORY. AC, DC, LINEAR ACTUATED, or AIR/OIL AVAILABLE.  
MODEL NUMBERS WITH THE SUFFIX "A" ARE SHIPPED KNOCK-DOWN