

## Three Ball Tow Hitch

The Three Ball Hitch can easily be attached to a fork truck base and used in a wide variety of applications. The unit features three different sized ball hitches on one unit for user convenience. Steel construction with powder coat black finish. Capacities below are uniform capacities.

MODEL NUMBER	BALL 1 SIZE	BALL 1 CAPACITY	BALL 2 SIZE	BALL 2 CAPACITY	BALL 3 SIZE	BALL 3 CAPACITY	WEIGHT (POUND)
<b>HITCH-3B</b>	2 <sup>5</sup> / <sub>16</sub> "	7,500 lb.	2"	3,500 lb.	1 <sup>7</sup> / <sub>8</sub> "	2,000 lb.	11

**THREE BALL TOW HITCH**  
model HITCH-3B



## Hooks with Shackle

Easily connects to Hoisting Hooks, Hook Plates, or Booms. Available in swivel or rigid styles. Variety of capacities available. Forged steel construction.

MODEL NUMBER	DESCRIPTION	UNIFORM LIFTING CAPACITY	WEIGHT (POUND)
<b>HOOK-S-4</b> Ⓢ	LATCHING SWIVEL HOOK WITH SHACKLE	4,000 lb.	4
<b>HOOK-S-6</b> Ⓢ	LATCHING SWIVEL HOOK WITH SHACKLE	6,000 lb.	5
<b>HOOK-S-10</b> Ⓢ	LATCHING SWIVEL HOOK WITH SHACKLE	10,000 lb.	14
<b>HOOK-R-4</b> Ⓢ	RIGID GRAB HOOK WITH SHACKLE	4,000 lb.	3

**RIGID HOOK WITH SHACKLE**  
model HOOK-R-4



**SWIVEL HOOK WITH SHACKLE**  
model HOOK-S-4




## Forklift Hitch

Forklift Hitch is a superb addition to most manufacturing and maintenance facilities. Strong steel construction allows for long term use, even in the harshest of conditions. 3-ball hitch attachment can be removed and rotated to desired ball. Maximum push capacity for each ball size; 1<sup>7</sup>/<sub>8</sub>" = 2,000 lb., 2" = 3,500 lb., 2-5/16" = 7,500 lb. The hitch includes a yellow finish for clear visibility. To use slide the forklift forks in to the unit and secure safety chain to forklift. Once in place, the unit is ready to be hitched to the desired equipment. Includes 56" long chain to secure to forklift. Not intended for pulling.

MODEL NUMBER	OVERALL SIZE (W x L x H)	USABLE FORK POCKET (W x H)	MAXIMUM TONGUE LOAD	WEIGHT (POUND)
<b>FTTM-2</b>	14 <sup>1</sup> / <sub>2</sub> " x 20 <sup>9</sup> / <sub>16</sub> " x 8 <sup>1</sup> / <sub>16</sub> "	4 <sup>5</sup> / <sub>16</sub> " x 11 <sup>1</sup> / <sub>16</sub> "	1,500 lb.	44

**FORK LIFT HITCH**  
model FTTM-2



## Bag Lifter

The Bag Lifter is ideal for industrial and manufacturing settings. The unit is constructed of powder coated steel for durability and added strength. The lifter can be used with the center mounted hook point for balanced lifting capabilities with an overhead hoist or with a forklift by utilizing the attached fork pockets (retaining strap included). After choosing which lifting style is best, secure the loops of the bag to the four strap points for safe maneuvering and transporting.

MODEL NUMBER	OVERALL SIZE (W x L x H)	UNIFORM CAPACITY	WEIGHT (POUND)
<b>BBL-4</b>	53 <sup>1</sup> / <sub>2</sub> " x 39 <sup>15</sup> / <sub>16</sub> " x 10 <sup>7</sup> / <sub>16</sub> "	4,000 lb.	118

**BAG LIFTER**  
model BBL-4




## Loading Platforms for Fork Truck

Allows fork trucks to load/unload items into trucks and trailers. Maximum uniform weight capacity is 2,000 pounds. (dependent on fork truck capacity). Includes 12" fold-down lip to help with transition. Side guard toeboards are 6" high. Four tie-down rings are included for securing equipment (tie downs not included). Diamond plate floor for extra traction. Safety restraint is included to secure platform to fork truck. Steel construction with blue baked-in powder-coated toughness.


MODEL NUMBER	USABLE PLATFORM SIZE (W x L)	UNIFORM CAPACITY	USABLE FORK POCKET SIZE (W x H)	WEIGHT (POUND)
<b>FTLP-5454</b>	54" x 54"	2,000 lb.	7 <sup>1</sup> / <sub>2</sub> " x 2 <sup>1</sup> / <sub>2</sub> "	337
<b>FTLP-5454-HR*</b>	51" x 48 <sup>1</sup> / <sub>2</sub> "	2,000 lb.	7 <sup>1</sup> / <sub>2</sub> " x 2 <sup>1</sup> / <sub>2</sub> "	407

\*FEATURES HANDRAIL ON TWO SIDES, BACK MESH SCREEN, & CHAINS

**model FTLP-5454**




**model FTLP-5454-HR**



## Fork Extension Storage Rack

Install or remove fork extensions without lifting, pushing, or getting off the fork truck. Easy to use: A) Drive in so tips of forks are over elevated bar. B) Lower forks until they nest in channel in base of rack. C) Back fork truck out of fork restraining straps. Fork extensions not included.

MODEL NUMBER	OVERALL SIZE (W x D x H)	MINIMUM / MAXIMUM FORK EXTENSION LENGTH	WEIGHT (POUND)
<b>FORK-R-54</b> Ⓢ	40" x 46" x 54"	60" / 96"	165



**model FORK-R-54**

