



These instructions and the images herein are proprietary. Any unauthorized reproduction is prohibited.

VANOTANK-SYNCRO

Syncro Fuel Tank Reseal

The installation of this kit requires the full removal of the engine and transmission of the vehicle. This kit is for expert/professional installation ONLY.

Note About Ear Clamps: These clamps require a dulled pair of end-nippers (or Oetiker pinchers) for installation. These clamps are *far* superior to "standard" clamps—they don't cut into the fuel line, and they provide even force around the circumference of the hose. These clamps are also unable to loosen like screw-type clamps.

Kit Contents:

- 7.3mm Fuel Hose (4.5m)
- 5.5mm Fuel Hose (3.5m)
- 12mm Fuel Hose (1m)
- 7.3mm In-tank Fuel Hose (0.5m)
- Filler Neck Grommet (1)
- Fuel Sender Grommet (2)
- Breather System T-fitting (1)
- 14mm Clamp (6)
- 15.7mm Clamp (8)
- 21mm Clamp (6)

To the right is a brief diagram of tank disassembly.

Below is a diagram showing two views of the fuel tank. Labeled in green are the fuel lines that will be replaced; labeled in blue are the gaskets replaced; and labeled in red are the ear clamps to be replaced. When installing the filler neck grommet, be sure the inner lip is in place by feeling around the seal. You may feel a bump or small distortion, meaning the grommet is not seated properly and needs adjusting.

