

Importator consumabile tipografice
Hartie & Carton
Producator adezivi
Producator ambalaje



## TECHNICAL DATA SHEET

## JELLY/ANIMAL GLUE

ISO9001-2008certified

PRODUCT CODE: RY29002

**APPLICATION:** 

RY29002 jelly glue is suitable for automatic box or book cover making machinery. It is applicable for laminating paper with paper board. Applicable for machine speed around 20~25pcs/min.

TECHNICAL PROPERTIES

**Appearance** Brown block

**Brookfield Viscosity** (RVF-20RPM-SP2)

About 600~700+/-10 mPa.s@60°C

**FEATURES** easy to operate, excellent viscosity, good flexibility, fast dry

## **USE INSTRUCTIONS:**

1. Melt the glue completely in 60°C

2. Add 5~10% water to the melted glue

3. Recommended operation temperature: 55-60°C.

4. It should not be mixed with any other type of adhesive.

5. The cover of glue tank should be closed lest the adhesive might be polluted.

**Solid Content** 

56~58%

PH Value

About 5,5~7,0

STORAGE: 6 months in a clean, cool, dry place, in

its original package at an average temperature of  $25^{\circ}$ C or below. Storage temperature should not

exceed 35°C.

**CLEAN-UP:** Mineral oil or paraffin wax, not to exceed flash point

as stated on the MSDS, followed by a thorough purge

with the adhesive itself.

**SAFETY:** MSDS should be consulted for proper handling

before use. Wear safety gloves and goggles when

handling molten adhesive.

**PACKAGING** 

2,5kg/bag, 25kg/carton