



VECTORIAL TRADE

Importator consumabile tipografice  
Hartie & Carton  
Producator adezivi  
Producator ambalaje



office@agpvectorial.ro



www.agpvectorial.ro



0744895932 / 0785276492

## Technical Data Sheet

### DEVELOPER FOR THERMAL CTP AND CTcP(UV-CTP) PLATES

#### READY-TO-USE

#### CHARACTERISTICS:

Excellent developing results. It contains aluminium protectors. Suitable to all plates. It keeps clean Plates Processors from encrustations. High stability.

#### APPLICATION:

Product is ready-to-use and it can be used both as developer and as replenisher. We suggest anyhow to replace the bath at least once a month. The product is suitable to following plates, with relevant working temperatures:

	Brand and type of plate	Working Temperature	Contact time	Replenishm. ml/mq	Antiox. ml/mq
<b>THERMAL CTP PLATES</b>	KODAK CAPRICORN VT	22 ° C (± 1°)	25-30''	100-120	120-140
	HUAFENG CTP THERMAL	21 ° C (± 1°)	25-30''	100-120	120-140
	FUJI BRILLIA LH-PCE	23 ° C (± 1°)	30-35''	100-120	120-140
	IPAGSA SF 25	22 ° C (± 1°)	25-35''	100-120	120-140
	HUAGUANG TP II	22 ° C (± 1°)	25-30''	100-120	120-140
<b>CTcP PLATES</b>	FUJI FDT 508	22 ° C (± 1°)	25-30''	100-120	120-140
	ABEZETA ULTIMATE	22 ° C (± 1°)	25-30''	100-120	120-140
	IPAGSA ECO 88 S	23 ° C (± 1°)	25-35''	100-120	120-140
	AGFA ALUVA P	23 ° C (± 1°)	30-35''	100-120	120-140
	HUAGUANG UVP H	22 ° C (± 1°)	25-30''	100-120	120-140

Physical state : <b>LIQUID</b>	Colour : <b>COLOURLESS</b>	Odour : <b>ODOURLESS</b>	pH: <b>&gt; 13</b>
Conductivity at 25°C: <b>98 – 102 mS</b>	Boiling Point : <b>100°C</b>	Flash point : <b>NOT FLAMMABLE</b>	Water solubility : <b>COMPLETE</b>

**PRECAUTIONS:**

**Before use, read carefully Material Safety Data Sheet.** We suggest to clean the Plate Processor with SOLVENT. Rinse carefully to eliminate incrustations which could come off using the product.

**PACKING:**

Canister 20 litres