# CRAFTMADE

## **ASSEMBLY & INSTALLATION INSTRUCTIONS FOR # 26601**

Please read carefully and save these instructions, as you may need them at a later date.

#### CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

#### GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

### **ASSEMBLY AND INSTALLATION**

- 1. At the center of the BACK PLATE (2) there are eight perforated slots. Knock out the set matches your OUTLET BOX (1).
- 2. Screw the #8-32 FIXTURE MOUNTING SCREWS (13) into the BACK PLATE
- 3. Carefully pass the power supply (6&8) wires and the SUPPLY GROUND WIRE (2) to the OUTLET BOX (1) with MOUNTING SCREWS (3).
- 4. Attach the BLACK SUPPLY WIRE (8) to the SMOOTH (or BLACK) FIXTURE  $\mathbf{TTTD} = \mathbf{O} = \mathbf{O}$  $\mathbf{T} = \mathbf{T} + \mathbf{T} +$

(2) and thread the #8-32 HEX NUTS (14) onto the FIXTURE MOUNTING SCREWS (13), as shown. Secure the position of the FIXTURE MOUNTING SCREWS (13) by tightening the HEX NUTS (14) against the BACK PLATE (2).

(5) through the center hole of the BACK PLATE (2). Secure the BACK PLATE

### **ASSEMBLY AND INSTALLATION (Continued)**

6. Slide the GLASS SHADE(17) over the SOCKET(16), secure with the SOCKET RING(18).

7. Screw light bulb into the socket and make sure it does not exceed the maximum wattage specified on the fixture's wattage rating label, MAXIMUM 100W.

#### INSTALLATION IS NOW COMPLETED

