ASSEMBLY AND INSTALLATION (Continued)

ASSEMBLY & INSTALLATION INSTRUCTIONS FOR G9 BASE 1V&2V

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

- 1. NIPPLE (12) into the CROSS BAR (9) as shown.
- Carefully pass the power supply (6&8) wires and the SUPPLY GROUND WIRE
 (3) .Secure the CROSS BAR(9) to the OUTLET BOX (1) with MOUNTING SCREWS (11).
- 3. Attach the BLACK SUPPLY WIRE (2) to the SMOOTH (or BLACK) FIXTURE LEAD WIRE (6) by using the WIRE CONNECTOR (5). At the same manner, attach the WHITE SUPPLY WIRE (4) to the RIBBED (or WHITE) FIXTURE LEAD WIRE (8). Loop the FIXTURE GROUND WIRE (7) around the GROUND SCREW (10) of the CROSS BAR(9). (Note: Be sure to provide an extra 3" length of the FIXTURE GROUND WIRE (4) for connection to the SUPPLY GROUND WIRE (3).) Tighten the GROUND SCREW (10). Connect the remaining FIXTURE GROUND WIRE (7) to the SUPPLY GROUND WIRE (3) using a WIRE CONNECTOR (5). Place wiring and connections inside the OUTLET BOX (1).

- 4. Place the BACKPLATE(14) onto the NIPPLE(12), and secure it into place using the FINIAL NUT(16) provided.
- 5. Slide the GLASS SHADE(17) over the SOCKET(15), secure with the SOCKET RING(18).
- 6. Screw light bulb into the socket and make sure it does not exceed the maximum wattage specified on the fixture's wattage rating label.

INSTALLATION IS NOW COMPLETED

