I Specifications

1 Specifications			
		UL	CE
XLC-2000/3000*		XLC-2000/3000	XLC-2000/3000
General	Power Supply	AC120V / 60Hz	220V ~ 240V / 50Hz
	Power Consumption	1270W	1670W
	Power Cord Length	4 ft.	1.8m
	Water Pressure	10.7 ~ 106.6 psi	0.75 ~ 7.5kgf/cm ²
	Elongated Dimension (WxDxH)	16.0x20.8x5.7	406X528X145
	Round Dimension (WxDxH)	16.0x19.5x5.7	406X496X14
	Small Dimension (WxDxH)	16.0x18.5x5.7	406X470X14
	Weight	10.1lb	4.6kg
Wash	Power Consumption	1200W	1600W
	Wash Volume	0.16gal / min.	0.7 L/ min.
	Bidet Volume	0.16gal / min.	0.7 L / min.
	Sitz Bath Volume	0.16gal / min.	0.7 L / min.
	Nozzle Position Control	5 Steps	5 Steps
	Water Pressure Control	5 Steps	5 Steps
	Water Temp. Control	4 Steps	4 Steps
	Safety Device	Temp. Sensor, Bimetal, Fuse	Temp. Sensor, Bimetal, Fuse
Dry	Power Consumption	250W	250W
	Dry Temp. Control	5 Steps	5 Steps
	Safety Device	Bimetal, Fuse	Bimetal, Fuse
Heated Seat	Power Consumption	55W	55W
	Seat Temp. Control	4 Steps	4 Steps
	Safety Device	Temp. Sensor, Fuse	Temp. Sensor, Fuse
	Seat Sensor	Body Sensor	Body Sensor

^{*}Available in round or elongated seat sizes





The Bathroom of the Future...Is Here Today







03 Points



Ceramic Instant Heating

The newest and most energy efficient way to heat water – continuously heats water for as long as you need



Cold-Warm / Sitz Bath

Exclusive feature to relieve many medical conditions



Child Wash

Specialized nozzle position, water pressure/ temperature for sensitive children and elderly people





Bubble Wash

Aerated water wash aids cleansing



Pulse

Pulse wash repeatedly cycles from weak to strong



Self-Cleaning

To wash and maintain clean nozzle that operates before and after every use



Adjustable Nozzle Position

Users can adjust nozzle position to desired setting



Compact Design

Fits most 1 and 2 piece toilets. Sleek-Low profile-Contoured design



Self-Diagnosis

Self-diagnosis function continuously monitors operation



Seat Sensor

User must be sitting to activate controls



Water Purifying Filter

Specialized ion water filter (optional)



Vertical Nozzles

Vertical nozzles provide improved hygiene use



Control Arm XLC-2000

Easy touch and simple waterproof switching



Remote Control XLC-3000

Easy touch and simple waterproof switching



Detachable Main Body

It is easy to install and detach for cleaning or moving

